



B43740A9828M7 Information

Heisener.com

Part Number B43740A9828M7
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 8200UF 20% 400V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43740A9828M7 Specifications

Manufacturer Part Number B43740A9828M7 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Screw Terminals Series B43740 Capacitance 8200μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 13 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance 16 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 7.547" (191.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43740 Capacitance 8200µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 13 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 16 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) 7.547" (191.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43740A9828M7
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43740 Capacitance 8200µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 13 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance 16 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 7.547" (191.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43740Capacitance\$200µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)13 mOhm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20A @ 100HzRipple Current - High Frequency-Impedance16 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)7.547" (191.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series B43740 Capacitance 8200μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 13 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance 16 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 7.547" (191.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 8200μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 13 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance 16 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 7.547" (191.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 13 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance 16 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 7.547" (191.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	B43740
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Roon Hrs @ 100Hz Food of the Common of the	Capacitance	8200µF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Rio00 Hrs @ 100Hz 6000 Hrs @ 105°C 6000 Hrs @ 1000 Hrs @ 10	Tolerance	±20%
Lifetime @ Temp. Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 6000 Hrs @ 105°C - 6000 Hrs @ 105°C 6000 Hrs @ 1000 Hrs @ 1000 Hrs ellower 6000 Hrs ellower 6000 Hrs ellower 6000 Hrs ellower 6000 Hrs ellower 600 Hrs ell	Voltage - Rated	400V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Impedance Inpedance Item Spacing Ingel Current Ingel Ingel Current Ingel Ingel Current Ingel Inge	ESR (Equivalent Series Resistance)	13 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	6000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Inpedance Item Ohms Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Inpedance Iead Spacing Ince Size / Dimension Size / Dimension Surface Mount Land Size Mounting Type Chassis Mount Package / Case 20A @ 100Hz - 16 mOhms 1.248" (31.70mm) 3.028" Dia (76.90mm) 7.547" (191.70mm) - Chassis Mount Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance In Mohms Lead Spacing In Lead Spacin	Applications	General Purpose
Impedance16 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)7.547" (191.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	20A @ 100Hz
Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 7.547" (191.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 7.547" (191.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	16 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.028" Dia (76.90mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	7.547" (191.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B43740A9828M7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43740A9828M7 Payment Methods



















B43740A9828M7 Shipping Methods













If you have any question about B43740A9828M7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com