



### **B43741A9338M000 Information**

Heisener.com

Part NumberB43741A9338M000ManufacturerEPCOS (TDK)

**Category** Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 3300UF 20% 400V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43741A9338M000 Specifications**

Manufacturer Part Number         B43741A9338M000           Manufacturer         EPCOS (TDK)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         B43741           Capacitance         3300µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         30 mOhm @ 100Hz           Lifetime @ Temp.         6000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         10.6A @ 100Hz           Ripple Current - High Frequency         -           Impedance         45 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.531" Dia (64.30mm)           Height - Seated (Max)         4.693" (119.20mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         B43741           Capacitance         3300µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         30 mOhm @ 100Hz           Lifetime @ Temp.         6000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         10.6A @ 100Hz           Ripple Current - High Frequency         -           Impedance         45 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.531" Dia (64.30mm)           Height - Seated (Max)         4.693" (119.20mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer Part Number	B43741A9338M000
Package         Radial, Can - Screw Terminals           Series         B43741           Capacitance         3300μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         30 mOhm @ 100Hz           Lifetime @ Temp.         6000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         10.6A @ 100Hz           Ripple Current - High Frequency         -           Impedance         45 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.531" Dia (64.30mm)           Height - Seated (Max)         4.693" (119.20mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
Package Radial, Can - Screw Terminals  Series B43741  Capacitance 3300µF  Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 30 mOhm @ 100Hz  Lifetime @ Temp. 6000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 10.6A @ 100Hz  Ripple Current - High Frequency -  Impedance 45 mOhms  Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.531" Dia (64.30mm)  Height - Seated (Max) 4.693" (119.20mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series         B43741           Capacitance         3300µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         30 mOhm @ 100Hz           Lifetime @ Temp.         6000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         10.6A @ 100Hz           Ripple Current - High Frequency         -           Impedance         45 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.531" Dia (64.30mm)           Height - Seated (Max)         4.693" (119.20mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance       3300μF         Tolerance       ±20%         Voltage - Rated       400V         ESR (Equivalent Series Resistance)       30 mOhm @ 100Hz         Lifetime @ Temp.       6000 Hrs @ 105°C         Operating Temperature       -40°C ~ 105°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       10.6A @ 100Hz         Ripple Current - High Frequency       -         Impedance       45 mOhms         Lead Spacing       1.122" (28.50mm)         Size / Dimension       2.531" Dia (64.30mm)         Height - Seated (Max)       4.693" (119.20mm)         Surface Mount Land Size       -         Mounting Type       Chassis Mount         Package / Case       Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 30 mOhm @ 100Hz  Lifetime @ Temp. 6000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 10.6A @ 100Hz  Ripple Current - High Frequency -  Impedance 45 mOhms  Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.531" Dia (64.30mm)  Height - Seated (Max) 4.693" (119.20mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	B43741
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  6000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  45 mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Round Hook and 100Hz  Low Frequency  -  Chassis Mount  Radial, Can - Screw Terminals	Capacitance	3300µF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  6000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  10.6A @ 100Hz  Ripple Current - High Frequency  Impedance  45 mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  4.693" (119.20mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Riono Hrs @ 105°C  -40°C ~ 100°C  -40°C ~ 100	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  45 mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  6000 Hrs @ 105°C  -40°C ~ 105°C  Following  Rolling  General Purpose  10.6A @ 100Hz  1.122" (28.50mm)  2.531" Dia (64.30mm)  4.693" (119.20mm)  Chassis Mount  Radial, Can - Screw Terminals	Voltage - Rated	400V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 10.6A @ 100Hz Ripple Current - High Frequency - Impedance 45 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.531" Dia (64.30mm) Height - Seated (Max) 4.693" (119.20mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	30 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 10.6A @ 100Hz  Ripple Current - High Frequency -  Impedance 45 mOhms  Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.531" Dia (64.30mm)  Height - Seated (Max) 4.693" (119.20mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	6000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 10.6A @ 100Hz  Ripple Current - High Frequency	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 45 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.531" Dia (64.30mm) Height - Seated (Max) 4.693" (119.20mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 45 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.531" Dia (64.30mm) Height - Seated (Max) 4.693" (119.20mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance45 mOhmsLead Spacing1.122" (28.50mm)Size / Dimension2.531" Dia (64.30mm)Height - Seated (Max)4.693" (119.20mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	10.6A @ 100Hz
Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.531" Dia (64.30mm)  Height - Seated (Max) 4.693" (119.20mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.531" Dia (64.30mm)  Height - Seated (Max) 4.693" (119.20mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	45 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.122" (28.50mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.531" Dia (64.30mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.693" (119.20mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### **B43741A9338M000 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## B43741A9338M000 Payment Methods





















## B43741A9338M000 Shipping Methods













If you have any question about B43741A9338M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com