



#### **B43750A4278M7 Information**

Manufacturer
Category

Part Number B43750A4278M7
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 2700UF 20% 350V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43750A4278M7 Specifications**

Manufacturer Part Number         B43750A4278M7           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can - Screw Terminals           Series         B43750           Capacitance         2700μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         24 mOhm @ 100Hz           Lifetime @ Temp.         8000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         16A @ 100Hz           Ripple Current - High Frequency         -           Impedance         13 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.028" Dia (76.90mm)           Height - Seated (Max)         4.185" (106.30mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43750 Capacitance 2700µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 24 mOhm @ 100Hz Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency Inpedance 13 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43750A4278M7
Aluminum Electrolytic Capacitors  Package Radial, Can - Screw Terminals  Series B43750  Capacitance 2700µF  Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) 24 mOhm @ 100Hz  Lifetime @ Temp. 8000 Hrs @ 105°C  Operating Temperature - Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 16A @ 100Hz  Ripple Current - High Frequency - Impedance 13 mOhms  Lead Spacing 1.248" (31.70mm)  Size / Dimension 3.028" Dia (76.90mm)  Height - Seated (Max) 4.185" (106.30mm)  Surface Mount Land Size  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43750Capacitance2700µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)24 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16A @ 100HzRipple Current - High Frequency-Impedance13 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)4.185" (106.30mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series         B43750           Capacitance         2700μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         24 mOhm @ 100Hz           Lifetime @ Temp.         8000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         16A @ 100Hz           Ripple Current - High Frequency         -           Impedance         13 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.028" Dia (76.90mm)           Height - Seated (Max)         4.185" (106.30mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         2700μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         24 mOhm @ 100Hz           Lifetime @ Temp.         8000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         16A @ 100Hz           Ripple Current - High Frequency         -           Impedance         13 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.028" Dia (76.90mm)           Height - Seated (Max)         4.185" (106.30mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) 24 mOhm @ 100Hz  Lifetime @ Temp. 8000 Hrs @ 105°C  Operating Temperature - Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 16A @ 100Hz  Ripple Current - High Frequency - Impedance 13 mOhms  Lead Spacing 1.248" (31.70mm)  Size / Dimension 3.028" Dia (76.90mm)  Height - Seated (Max) 4.185" (106.30mm)  Surface Mount Land Size - Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	B43750
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  8000 Hrs @ 105°C  Operating Temperature  - Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  1.248" (31.70mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Capacitance	2700μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  Polarization  Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  Polar  8000 Hrs @ 100Hz  8000 Hrs @ 105°C  8000 Hrs @ 105°C  1048  105°C  1048  1048  1048  1048  1048  105°C  1048  104	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  - Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  Roll Hrs @ 105°C  General Purpose  16A @ 100Hz  17A @ 100Hz  18A @ 100Hz  19A @ 105°C  19A @ 105°  19A	Voltage - Rated	350V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance I3 mOhms Lead Spacing I.248" (31.70mm) Size / Dimension Jize / Dimension Jize / Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	24 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency 16A @ 100Hz Ripple Current - High Frequency Impedance 13 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.185" (106.30mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	8000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  13 mOhms  Lead Spacing  1.248" (31.70mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Operating Temperature	-
Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 13 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.185" (106.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 13 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.185" (106.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance 13 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.185" (106.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	16A @ 100Hz
Lead Spacing 1.248" (31.70mm)  Size / Dimension 3.028" Dia (76.90mm)  Height - Seated (Max) 4.185" (106.30mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.028" Dia (76.90mm)  Height - Seated (Max) 4.185" (106.30mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	13 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.028" Dia (76.90mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.185" (106.30mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### B43750A4278M7 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43750A4278M7 Payment Methods**



















## **B43750A4278M7 Shipping Methods**













If you have any question about B43750A4278M7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com