



B43750A5138M7 Information

Heisener.com

Part Number B43750A5138M7
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1300UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43750A5138M7 Specifications

Manufacturer Part Number B43750A5138M7 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Screw Terminals Series B43750 Capacitance 1300µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 46 mOhm @ 100Hz Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 14.3A @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals			
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43750 Capacitance 1300µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 46 mOhm @ 100Hz Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 14.3A @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43750A5138M7	
Package Radial, Can - Screw Terminals Series B43750 Capacitance 1300μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 46 mOhm @ 100Hz Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 14.3A @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)	
Package Radial, Can - Screw Terminals Series B43750 Capacitance 1300µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 46 mOhm @ 100Hz Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 14.3A @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors	
Series B43750 Capacitance 1300μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 46 mOhm @ 100Hz Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 14.3A @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors	
Capacitance 1300μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 46 mOhm @ 100Hz Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 14.3A @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals	
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 46 mOhm @ 100Hz Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 14.3A @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	B43750	
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 8000 Hrs @ 100Hz Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Capacitance	1300μF	
ESR (Equivalent Series Resistance) Lifetime @ Temp. 8000 Hrs @ 105°C Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case R000 Hrs @ 100Hz 8000 Hrs @ 105°C - 8	Tolerance	±20%	
Lifetime @ Temp. Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Robert - Was an analysis of the state of the	Voltage - Rated	450V	
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Tambedance	ESR (Equivalent Series Resistance)	46 mOhm @ 100Hz	
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 14.3A @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	8000 Hrs @ 105°C	
Applications General Purpose Ripple Current - Low Frequency 14.3A @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-	
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance T3 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar	
Ripple Current - High Frequency Impedance 73 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose	
Impedance73 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)3.843" (97.60mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	14.3A @ 100Hz	
Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-	
Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 3.843" (97.60mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	73 mOhms	
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)	
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.583" Dia (91.00mm)	
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	3.843" (97.60mm)	
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-	
-	Mounting Type	Chassis Mount	
	Package / Case	Radial, Can - Screw Terminals	
Report errors?		Report error	ors?

B43750A5138M7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43750A5138M7 Payment Methods



















B43750A5138M7 Shipping Methods













If you have any question about B43750A5138M7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com