



B43761A6108M000 Information

Heisener.com

For Reference Only

Manufacturer EPCOS (TDK)

Part Number B43761A6108M000

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1000UF 20% 500V SCREW

Radial, Can - Screw Terminals **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43761A6108M000 Specifications

Manufacturer Part Number B43761A6108M000 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43761 Capacitance 1000µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.2A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43761 Capacitance 1000µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.2A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43761A6108M000
Package Radial, Can - Screw Terminals Series B43761 Capacitance 1000μF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.2A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
Package Radial, Can - Screw Terminals Series B43761 Capacitance 1000µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.2A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series B43761 Capacitance 1000µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.2A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 1000μF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.2A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.2A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Rated (Max) Radial, Can - Screw Terminals	Series	B43761
Voltage - Rated500VESR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.2A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.031" Dia (51.60mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	1000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 5.2A @ 100Hz Ripple Current - High Frequency Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 4.201" (106.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Robot Hrs @ 100Hz Foundary Foundary Foundary Avor 105°C Foundary	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Frequency Fipple Current - High Frequency Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case 6000 Hrs @ 105°C 6000 Hrs @ 105° 6000 Hrs @ 1	Voltage - Rated	500V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency S.2A @ 100Hz Ripple Current - High Frequency Impedance I10 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	75 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.2A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	6000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency Fipple Current - High Frequency Impedance In mohms Lead Spacing Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case General Purpose 5.2A @ 100Hz - 10 mOhms - 110 mOhms 2.874" (22.20mm) 2.031" Dia (51.60mm) 4.201" (106.70mm) Chassis Mount Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 110 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance Inpedance Inpe	Applications	General Purpose
Impedance110 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.031" Dia (51.60mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	5.2A @ 100Hz
Lead Spacing 0.874" (22.20mm) Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.031" Dia (51.60mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	110 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	0.874" (22.20mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.031" Dia (51.60mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.201" (106.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
· · · · · · · · · · · · · · · · · · ·		Report errors?

B43761A6108M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43761A6108M000 Payment Methods





















B43761A6108M000 Shipping Methods













If you have any question about B43761A6108M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com