



B43821A4684M Information

Heisener.com

Part Number B43821A4684M Manufacturer EPCOS (TDK) Category

Aluminum Electrolytic Capacitors

Description CAP ALUM 0.68UF 20% 350V RADIAL

Package

For the pricing/inventory/lead time, please contact

Capacitors

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43821A4684M Specifications

Manufacturer Part Number B43821A4684M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B43821 Capacitance 0.68µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 273 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 18mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	L	
Category Capacitors Package Radial, Can Series B43821 Capacitance 0.68µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 273 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 18mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B43821A4684M
Package Radial, Can Series B43821 Capacitance 0.68μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 273 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 18mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B43821 Capacitance 0.68µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 273 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 18mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B43821 Capacitance 0.68μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 273 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 18mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 0.68µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 273 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 18mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 273 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 18mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B43821
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case R3000 Hrs @ 120Hz 273 Ohm @ 120Hz 273 Ohm @ 120Hz 275 Ohm @ 120Hz 276 Ohm @ 120Hz 277 Ohm @ 120Hz 278 Ohm @ 120Hz 278 Ohm @ 120Hz 279 Ohm @ 120Hz 270 Ohm	Capacitance	0.68μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 273 Ohm @ 120Hz 3000 Hrs @ 85°C -25°C ~ 85°C Polar -25°C ~ 85°C -2	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 3000 Hrs @ 85°C -25°C ~ 85°C Beneral Purpose 18mA @ 120Hz - 10098" (2.50mm) 0.248" Dia (6.30mm) 0.472" (12.00mm) Through Hole Radial, Can	Voltage - Rated	350V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	273 Ohm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 18mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	3000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Ripple Current - Low Frequency	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	18mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43821A4684M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43821A4684M Payment Methods



















B43821A4684M Shipping Methods













If you have any question about B43821A4684M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com