



B43821F2225M Information

Heisener.com

Part Number B43821F2225M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 2.2UF 20% 250V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43821F2225M Specifications

Manufacturer Part NumberB43821F2225MManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43821Capacitance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 Ohm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Die office of the specific and the specific of	
Category Capacitors Package Radial, Can Series B43821 Capacitance 2.2µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 33mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer Part Number	B43821F2225M
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43821Capacitance2.2μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 Ohm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzRipple Current - High Frequency-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B43821 Capacitance 2.2µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 33mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole	Category	Capacitors
SeriesB43821Capacitance2.2μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 Ohm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance2.2µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 Ohm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 33mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole	Series	B43821
Voltage - Rated ESR (Equivalent Series Resistance) ESR (Equivalent Series Resistance) ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz 3000 Hrs @ 85°C -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 33mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole	Capacitance	2.2µF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 85 Ohm @ 120Hz 85 Ohm @ 120Hz -40°C ~ 85°C Polar -40°C ~ 85°C -60erral Purpose 33mA @ 120Hz -10erral Purpose 30mA @ 120Hz 30mA @ 120Hz -10erral Purpose 30mA @ 120Hz 30mA	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	250V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.098" (2.50mm) Size / Dimension O.248" Dia (6.30mm) Height - Seated (Max) O.472" (12.00mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	85 Ohm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 33mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	3000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type General Purpose 33mA @ 120Hz - 0.098" (2.50mm) 0.098" (2.50mm) 0.248" Dia (6.30mm) 0.472" (12.00mm) Through Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole	Applications	General Purpose
Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole	Ripple Current - Low Frequency	33mA @ 120Hz
Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole	Ripple Current - High Frequency	-
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 0.472" (12.00mm) - Through Hole	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole	Height - Seated (Max)	0.472" (12.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can	Mounting Type	Through Hole
	Package / Case	Radial, Can
Report errors?		Report errors?

B43821F2225M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43821F2225M Payment Methods



















B43821F2225M Shipping Methods













If you have any question about B43821F2225M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com