

B43851A2225M Information

Manufacturer EPCOS (TDK) Category Heisener.com

Aluminum Electrolytic Capacitors

Description CAP ALUM 2.2UF 20% 200V RADIAL

Package

Part Number B43851A2225M

Capacitors

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43851A2225M Specifications

Manufacturer Part Number B43851A2225M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B43851 Capacitance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	1	
Category Capacitors Package Radial, Can Series B43851 Capacitance 2.2µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B43851A2225M
Package Radial, Can Series B43851 Capacitance 2.2µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B43851 Capacitance 2.2μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B43851 Capacitance 2.2µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 2.2µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 85 Ohm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Series	B43851
Voltage - Rated ESR (Equivalent Series Resistance) Est Ohm @ 120Hz Frogrammer Folar Application Polar Applications General Purpose Earnel Purpose 23mA @ 120Hz Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Capacitance	2.2µF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar 3000 Hrs @ 120Hz General Purpose 23mA @ 120Hz - - - - - 0.098" (2.50mm) 0.248" Dia (6.30mm) 0.472" (12.00mm) Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 3000 Hrs @ 105°C - 0098" (2.50mm) 0.248" Dia (6.30mm) 0.472" (12.00mm) Through Hole Radial, Can	Voltage - Rated	200V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar	ESR (Equivalent Series Resistance)	85 Ohm @ 120Hz
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar General Purpose 1.00Hz 1.00H	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can General Purpose 23mA @ 120Hz - 0.098" (2.50mm) 0.098" (2.50mm) 0.248" Dia (6.30mm) 0.472" (12.00mm) Through Hole	Operating Temperature	-
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.098" (2.50mm) Size / Dimension O.248" Dia (6.30mm) Height - Seated (Max) O.472" (12.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Case - Case - Composition - Comp	Ripple Current - Low Frequency	23mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43851A2225M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43851A2225M Payment Methods



















B43851A2225M Shipping Methods













If you have any question about B43851A2225M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com