

## B43858C9476M

Request a Quote

#### B43858C9476M Information

Heisener.com	Part Number	B43858C9476M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 47UF 20% 400V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
Tor reference only		E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43858C9476M Specifications

Manufacturer Part NumberB43858C9476MManufacturer AEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanStriesB43858Capacitance404µTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime G Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency980mA @ 100kHzImpedance-Lied Spacing0.25°C ', 7.50mn)Size Afount Land Size-Mounting Type-Package Mount Land Size-Package JCase-Mounting Type-Package JCase-Package JCase- <t< th=""><th>-</th><th></th></t<>	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43858Capacitance47µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.255° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	Manufacturer Part Number	B43858C9476M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43858Capacitance47µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature25°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency980mA @ 100kHzImpedance-Liad Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Hight - Seated (Max)3.19° (33.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43858Capacitance47µFTolerance20%Voltage - Rated400VESR (Equivalent Series Resistance)000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°COperating Temperature25°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency980mA @ 100kHzImpedance0.25°T . 50mm)Siz / Dinension0.25°T . 50mm)Siz / Dinension0.25°T . 50mm)Siz / Dinension0.30° Dia (1.60mm)Height - Seated (Max)3.11° (3.50mm)Surface Mount Land Size-Mounting TypePincagePackage / CaseRadial, Can	Category	Capacitors
ArrowB4385Capacitance47μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Lifed Spacing0.295° (7.50mn)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)3.19° (33.50mm)Surface Mount Land Size-Mounting TypeFrough HolePokang Curse-Surface Mount Land Size-Surface Mount Land Size-Mounting TypeStal, Can		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRippe Current - Hugh Frequency980mA @ 100kHzImpedance-Liad Spacing0.25° (7.50mm)Size / Dimension0.30° Dia (16.00mm)Height - Seated (Max)3.19° (3.50mm)Surface Mount Land Size-Mounting TypeHrough HolePokage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Mipedance-Lead Spacing0630° Dia (16.00mm)Size / Dimension1.319° (33.50mm)Hight - Seated (Max)-Surface Mount Land Size-Mounting TypeRatial, Can	Series	B43858
Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime G Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Mapdance-Lead Spacing080mA @ 100kHzSize / Dimension0.255° (7.50mm)Size / Dimension0.309° Dia (16.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Nounting TypeFrequencePackage / CaseRatial, Can	Capacitance	47µF
ConstraintESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)5000 Hrs @ 105°CLifetime @ Temp25°C ~ 105°COperating TemperaturePolarPolarizationGeneral PurposeApplications-Ripple Current - Low Frequency-Mipedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Bipple Current - High Frequency980mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFuncePackage / CaseRadial, Can	Voltage - Rated	400V
Operating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Bipple Current - High Frequency980mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency980mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeApple Current - Low Frequency-Ripple Current - High Frequency980mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadia, Can	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency-Ripple Current - High Frequency980mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can	Polarization	Polar
Ripple Current - High Frequency980mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	980mA @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.319" (33.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### B43858C9476M Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **B43858C9476M Payment Methods**





If you have any question about B43858C9476M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com