

B43866A2476M

Request a Quote

B43866A2476M Information

Heisener.com	Part Number	B43866A2476M
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 47UF 20% 200V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43866A2476M Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43866Capacitance47µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)7.1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature9olarApplicationsGeneral PurposeRipple Current - High Frequency4.35mA @ 100kHzImpedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB43866Capacitance47µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)7.1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Lifed Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	B43866A2476M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43866Capacitance47μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)7.1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency435mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Sirface Mount Land Size-Package / CaseRatial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43866Capacitance47µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)7.1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency-Size / Dimension0.197" (5.00mm)Size / Dimension0.492° Dia (12.50mm)Size / Dimension1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesB43866Capacitance47μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)7.1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Lifed Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Bight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)7.1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Beight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated200VESR (Equivalent Series Resistance)7.1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency435mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	B43866
Voltage - Rated200VESR (Equivalent Series Resistance)7.1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Argelance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	47µF
Comparison7.1 Ohm @ 120HzESR (Equivalent Series Resistance)7.1 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Hippedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Kipple Current - High Frequency435mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	200V
Operating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency435mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	7.1 Ohm @ 120Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency435mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 125°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency435mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}C \sim 125^{\circ}C$
Ripple Current - Low Frequency-Ripple Current - High Frequency435mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency435mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
In a born in the second of t	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	435mA @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43866A2476M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43866A2476M Payment Methods





If you have any question about B43866A2476M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com