



B43866C1476M Information

Manufacturer EPCOS (TDK) Category Heisener.com

Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 47UF 20% 160V RADIAL

Package

Part Number B43866C1476M

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43866C1476M Specifications

Manufacturer Part Number B43866C1476M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B43866 Capacitance 47µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Operating Temperature 90lar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12,50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	L	
Category Capacitors Package Radial, Can Series B43866 Capacitance 47µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B43866C1476M
Aluminum Electrolytic Capacitors	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B43866 Capacitance 47μF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B43866 Capacitance 47µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 47μF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B43866
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Roon Hrs @ 125°C -40°C ~ 125°C	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polar Application Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar -40°C ~ 125°C -40°C ~ 125°	Voltage - Rated	160V
Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar General Purpose - 0.100	Lifetime @ Temp.	5000 Hrs @ 125°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 125°C
Ripple Current - Low Frequency - 300mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	300mA @ 100kHz
Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43866C1476M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43866C1476M Payment Methods



















B43866C1476M Shipping Methods













If you have any question about B43866C1476M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com