



### **B43866C2336M Information**

Heisener.com

Part Number B43866C2336M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 33UF 20% 250V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43866C2336M Specifications**

Manufacturer Part Number         B43866C2336M           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can           Series         B43866           Capacitance         33µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 125°C           Operating Temperature         40°C ~ 125°C           Polarization         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         280mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	<b>L</b>	
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         B43866           Capacitance         33µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 125°C           Operating Temperature         -40°C ~ 125°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         280mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	B43866C2336M
Package         Radial, Can           Series         B43866           Capacitance         33μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 125°C           Operating Temperature         -40°C ~ 125°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         280mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	EPCOS (TDK)
Package         Radial, Can           Series         B43866           Capacitance         33μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 125°C           Operating Temperature         -40°C ~ 125°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         280mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         B43866           Capacitance         33µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 125°C           Operating Temperature         -40°C ~ 125°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         280mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         33μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 125°C           Operating Temperature         -40°C ~ 125°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         280mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 125°C  Operating Temperature -40°C ~ 125°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency 280mA @ 100kHz  Impedance - Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	B43866
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 125°C  Operating Temperature  -40°C ~ 125°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  280mA @ 100kHz  Impedance  -  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Rount Land Size  Radial, Can	Capacitance	33μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 125°C  Operating Temperature  -40°C ~ 125°C  Polar  Application  Applications  General Purpose  Ripple Current - Low Frequency  - Ripple Current - High Frequency  280mA @ 100kHz  Impedance  - Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.492" Dia (12.50mm)  Height - Seated (Max)  1.063" (27.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 125°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Polar  -40°C ~ 125°C  -	Voltage - Rated	250V
Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 280mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency	Lifetime @ Temp.	5000 Hrs @ 125°C
Applications  Ripple Current - Low Frequency - Ripple Current - High Frequency 280mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 125°C
Ripple Current - Low Frequency - 280mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.492" Dia (12.50mm)  Height - Seated (Max)  1.063" (27.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size - Through Hole  Package / Case Radial, Can	Ripple Current - Low Frequency	-
Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Ripple Current - High Frequency	280mA @ 100kHz
Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

### B43866C2336M Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43866C2336M Payment Methods**



















## **B43866C2336M Shipping Methods**













If you have any question about B43866C2336M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com