

B43866C9685M

Request a Quote

B43866C9685M Information

Containance cards new	Part Number	B43866C9685M
		EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 6.8UF 20% 400V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43866C9685M Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43866Capacitance6.8µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature-25°C ~ 125°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency100mA @ 100kHzImpedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB43866Capacitance6.8µFColerance±20%6Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature-25°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Manufacturer Part Number	B43866C9685M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43866Capacitance6.8µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature-25°C ~ 125°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency100mA @ 100kHzImpedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43866Capacitance6.8µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature25°C ~ 125°CPolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency100mA @ 100kHzImpedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.669" (17.00mm)Straface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesB43866Capacitance6.8μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature-25°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-LinedAnce-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance 6.8µF Capacitance ±20% Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -25°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Size / Dimension 0.669" (17.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Katial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature-25°C ~ 125°CPolarrPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	B43866
Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature-25°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Pounting TypeRatial, Can	Capacitance	6.8µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature-25°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Pounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature-25°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	400V
Operating Temperature-25°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency100mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Bipple Current - High Frequency100mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	3000 Hrs @ 125°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency100mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-25°C ~ 125°C
Ripple Current - Low Frequency-Ripple Current - High Frequency100mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency100mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
In rest of a straigImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	100mA @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.669" (17.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43866C9685M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43866C9685M Payment Methods





If you have any question about B43866C9685M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com