



B43867A1107M Information

Manufacturer EPCOS (TDK)
Category Capacitors
Aluminum Elec

Aluminum Electrolytic Capacitors

Description CAP ALUM 100UF 20% 160V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Part Number B43867A1107M

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43867A1107M Specifications

Manufacturer Part Number B43867A1107M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B43867 Capacitance 100μF Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 140°C Operating Temperature - Operating Temperature - Oplarization General Purpose Ripple Current - Low Frequency 450mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	L	
Category Capacitors Package Radial, Can Series B43867 Capacitance 100µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 140°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 450mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B43867A1107M
Aluminum Electrolytic Capacitors	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B43867 Capacitance 100μF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 140°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 450mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B43867 Capacitance 100µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 140°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 450mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 100µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 140°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 450mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 140°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 450mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B43867
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 140°C Operating Temperature Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 140°C - 10	Capacitance	100μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 140°C Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 140°C General Purpose 450mA @ 120Hz	Tolerance	±20%
Lifetime @ Temp. Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 140°C - 000 Hrs @ 140° - 000	Voltage - Rated	160V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing O.295" (7.50mm) Size / Dimension Dia (16.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency A50mA @ 120Hz Ripple Current - High Frequency Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 140°C
Applications Ripple Current - Low Frequency 450mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	450mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43867A1107M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43867A1107M Payment Methods



















B43867A1107M Shipping Methods













If you have any question about B43867A1107M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com