

B43867A4226M

Request a Quote

B43867A4226M Information

Heisener.com	Part Number	B43867A4226M
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 22UF 20% 350V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43867A4226M Specifications

Manufacturer Part NumberB43867A4226MManufacturer CAFCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRdial, CanSeriesB43867Cogacitance2µFTolerance±20%Voltage - Rated350%ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-ApplicationsGeneral PurposeApplications315m A @ 100k HzRipple Current - High Frequency315m A @ 100k HzImpedance-Lided Spacing0.600° Dian (III)Size Abund Land Size-Surface Mount Land Size-Mounting TypeHrouge HalePackage Case-Mounting Type-Package Case-Ripule Caree Abund Size-Surface Mount Land Size-Package Case-Package CasePackage Case </th <th>-</th> <th></th>	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43867Capacitance22µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency315m A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Nounting TypeFirough HolePackage / CaseRadial, Can	Manufacturer Part Number	B43867A4226M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43867Capacitance22µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationGeneral PurposeApplications210mA @ 120HzRipple Current - Low Frequency315mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.063" (27.00mm)Hight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43867Capacitance22µFTolerance20%Voltage - RatedS50VESR (Equivalent Series Resistance)-Joerantig Temper1000 Hrs @ 140°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - Low Frequency315mA @ 100kHzRipple Current - High Frequency0.295° (7.50mm)Size / Dimension0.30° Dia (1.600mm)Size / Dimension1.063° (7.00mm)Signer Gurdus Land Size1.063° (7.00mm)Sindrace Mount Land Size-Mounting TypeMaida, CanPackage / CaseRadial, Can	Category	Capacitors
SeriesB43867Capacitance22µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency210mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can		Aluminum Electrolytic Capacitors
Capacitance22µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency315mA @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension1.063° Dia (16.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency210mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension1.063° (27.00mm)Height - Seated (Max)1.063° (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	B43867
Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency210mA @ 120HzBipple Current - High Frequency315mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFrequencePackage / CaseRatial, Can	Capacitance	22µF
ConstraintESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency210mA @ 120HzBipple Current - High Frequency315mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency210mA @ 120HzBipple Current - High Frequency315mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFuroug Radia, Can	Voltage - Rated	350V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency210mA @ 120HzBipple Current - High Frequency315mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency210mA @ 120HzRipple Current - High Frequency315mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 140°C
ApplicationsGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency210mA @ 120HzRipple Current - High Frequency315mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can	Operating Temperature	-
Ripple Current - Low Frequency210mA @ 120HzRipple Current - High Frequency315mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	210mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	315mA @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43867A4226M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43867A4226M Payment Methods



-2#4_ FedEx. @ CRC **E**H

If you have any question about B43867A4226M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com