

B43867A4395M

Request a Quote

B43867A4395M Information

Heisener.com	Part Number	B43867A4395M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 3.9UF 20% 350V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
I of Reference Only		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43867A4395M Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43867Capacitance3.9µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Operating Temperature000 Hrs @ 140°COperating Temperature6ApplicationsGeneral PurposeRipple Current - High Frequency97mA @ 100kHzImpedance-Lead Spacing0.197" (5.0mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.366" (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43867Capacitance3.9µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzNipple Current - High Frequency97mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Manufacturer Part Number	B43867A4395M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43867Capacitance3.9µFTolerance±20%Voltage - RatedSoVESR (Equivalent Series Resistance)000 Hrs @ 140°COperating Temperature1000 Hrs @ 140°COperating Temperature6eneral PurposeApplicationsGeneral PurposeRiple Current - Low Frequency6fmA @ 120HzNipedance-Linded Spacing0.197" (S.00mm)Siz / Dimension0.394" Dia (10.00mm)Siz / Dimension0.866" (22.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Package / CaseKadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43867Capacitance3.9µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationGeneral PurposeRiple Current - Low Frequency65mA @ 120HzRiple Current - High Frequency0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesB43867Capacitance3.9μFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance3.9µFColprance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzMippedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	B43867
Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzBipple Current - High Frequency97mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	3.9µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzBipple Current - High Frequency97mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeFachage / CasePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzNapedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	350V
Operating Temperature-Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzBipple Current - High Frequency97mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeFuncy HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzRipple Current - High Frequency97mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 140°C
ApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzRipple Current - High Frequency97mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency65mA @ 120HzRipple Current - High Frequency97mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	65mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	97mA @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43867A4395M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43867A4395M Payment Methods





If you have any question about B43867A4395M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com