



### **B43867F2476M Information**

Heisener.com

Part Number B43867F2476M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 47UF 20% 250V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43867F2476M Specifications**

Manufacturer Part Number         B43867F2476M           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can           Series         B43867           Capacitance         47µF           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 140°C           Operating Temperature         -           Operating Temperature         General Purpose           Ripple Current - Low Frequency         330mA @ 120Hz           Ripple Current - High Frequency         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	*	
Category         Capacitors           Package         Radial, Can           Series         B43867           Capacitance         47µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 140°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         330mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	B43867F2476M
PackageRadial, CanSeriesB43867Capacitance47μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency330mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
Package         Radial, Can           Series         B43867           Capacitance         47μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 140°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         330mA @ 120Hz           Ripple Current - High Frequency         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         B43867           Capacitance         47µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 140°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         330mA @ 120Hz           Ripple Current - High Frequency         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         47μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 140°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         330mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 140°C  Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 330mA @ 120Hz  Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)  Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B43867
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 140°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency330mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	47μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  Polarization  Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Polar  1000 Hrs @ 140°C  General Purpose  330mA @ 120Hz  -  -  -  -  -  -  -  0.295" (7.50mm)  0.630" Dia (16.00mm)  1.319" (33.50mm)  Surface Mount Land Size  -  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  - Polarization  Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Size / Dimension  Mounting Type  Mounting Type  Polar  - Ceneral Purpose  330mA @ 120Hz	Voltage - Rated	250V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.295" (7.50mm) Size / Dimension O.630" Dia (16.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar General Purpose General Purpose 120Hz 12	Lifetime @ Temp.	1000 Hrs @ 140°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  O.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  Radial, Can	Operating Temperature	-
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	330mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.630" Dia (16.00mm)  Height - Seated (Max) 1.319" (33.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.319" (33.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### B43867F2476M Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **B43867F2476M Payment Methods**





















## **B43867F2476M Shipping Methods**













If you have any question about B43867F2476M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com