

B43888C1226M

Request a Quote

B43888C1226M Information

Heisener.com	Part Number	B43888C1226M
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 22UF 20% 160V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
I of Reference Only		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43888C1226M Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43888Capacitance22µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationGeneral PurposeRipple Current - High Frequency380mA @ 100kHzImpedance-Lifetint - Seated (Max)0.394" Dia (10.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Package / CaseKaila, Can	-	
CapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB43888Capacitance22µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationGeneral PurposeRipple Current - Liw Frequency380mA @ 100kHzImpedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Manufacturer Part Number	B43888C1226M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43888Capacitance22µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationGeneral PurposeRipple Current - High FrequencyS80mA @ 100kHzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.669" (17.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43888Capacitance22µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationGeneral PurposeRipple Current - High Frequency-Ripple Current - High Frequency380mA @ 100kHzImpedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.669" (17.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesB43888Capacitance22µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Inpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Pounting TypeRiogh HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance22µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Size / Dimension0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Brapedance-Lided Spacing0.197" (5.00mm)Size / Dimension0.669" (17.00mm)Hight - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseSatial Can	Series	B43888
Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stapple Current - High Frequency380mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Capacitance	22µF
ComponentESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Bipple Current - High Frequency380mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeFracuencyPackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Bipple Current - High Frequency380mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	160V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency380mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeFunculationPackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency380mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	-
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency380mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency-Ripple Current - High Frequency380mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency380mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	380mA @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.669" (17.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43888C1226M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43888C1226M Payment Methods





If you have any question about B43888C1226M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com