

B43888D5106M

Request a Quote

B43888D5106M Information

Heisener.com	Part Number	B43888D5106M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 10UF 20% 450V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43888D5106M Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43888Capacitance10µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-ApplicationsGeneral PurposeRipple Current - High FrequencyS00mA @ 100kHzImpedance-Lifetine @ Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesB43888Capacitance10µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationGeneral PurposeApplicationsSolom A @ 100kHzRipple Current - High Frequency500mA @ 100kHzImpedance-Liegt - Seated (Max)0.492" Dia (12.50mm)Size / Dimension1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	B43888D5106M
Aluminu Electrolytic CapacitorsPackageRadial, CanSeriesB43888Capacitance10µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Operating Temperature-Operating TemperaturePolarPolarizationGeneral PurposeRiple Current - High FrequencyS00MA @ 100kHzRiple Current - High Frequency0.197" (5.00mm)Siz / Dimension0.197" (5.00mm)Siz / Dimension1.063" (27.00mm)Sirface Mount Land Size-Mounting TypeFrequencyPackage / CaseStail, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43888Capacitance10µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationGeneral PurposeRipple Current - Low FrequencyS00mA @ 100kHzRipple Current - High Frequency0197" (5.00mm)Size / Dimension0.197" (5.00mm)Size / Dimension1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesB43888Capacitance10µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Size / Dimension0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance10µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Size / Dimension0.492" Dia(12.50mm)Size / Dimension0.492" Dia(12.50mm)Height - Seated (Max)-Surface Mount Land Size-Nounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stopple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension1.063" (27.00mm)Hight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	B43888
Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Stopperature-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRating Can	Capacitance	10µF
Composition-ESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stopple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFriough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stopple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	450V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stoppe Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	-
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency-Ripple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	500mA @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43888D5106M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43888D5106M Payment Methods





If you have any question about B43888D5106M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com