



B58600C5010A004 Information

Heisener.com

Part Number B58600C5010A004 Manufacturer EPCOS (TDK)

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE SENSOR AEA 0.400 C27/2

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B58600C5010A004 Specifications

Manufacturer Part Number B58600C5010A004 Manufacturer EPCOS (TDK) Category Sensors, Transducers Package Die Series C27 Pressure Type Absolute Operating Pressure 5.8 PSI (40 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 120 mV (5V) Accuracy ±2% Voltage - Supply 1 V ~ 5 V Port Size - Port Style No Port Features - Termination Style Solder Pad Maximum Pressure 43.51 PSI (300 kPa) Operating Temperature -40°C ~ 135°C		
CategorySensors, TransducersPackageDieSeriesC27Pressure TypeAbsoluteOperating Pressure5.8 PSI (40 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 120 mV (5V)Accuracy±2%Voltage - Supply1 V ~ 5 VPort Size-Port StyleNo PortFeatures-Termination StyleSolder PadMaximum Pressure43.51 PSI (300 kPa)	Manufacturer Part Number	B58600C5010A004
PackageDieSeriesC27Pressure TypeAbsoluteOperating Pressure5.8 PSI (40 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 120 mV (5V)Accuracy±2%Voltage - Supply1 V ~ 5 VPort Size-Port StyleNo PortFeatures-Termination StyleSolder PadMaximum Pressure43.51 PSI (300 kPa)	Manufacturer	EPCOS (TDK)
PackageDieSeriesC27Pressure TypeAbsoluteOperating Pressure5.8 PSI (40 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 120 mV (5V)Accuracy±2%Voltage - Supply1 V ~ 5 VPort Size-Port StyleNo PortFeatures-Termination StyleSolder PadMaximum Pressure43.51 PSI (300 kPa)	Category	Sensors, Transducers
SeriesC27Pressure TypeAbsoluteOperating Pressure5.8 PSI (40 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 120 mV (5V)Accuracy±2%Voltage - Supply1 V ~ 5 VPort Size-Port StyleNo PortFeatures-Termination StyleSolder PadMaximum Pressure43.51 PSI (300 kPa)		Pressure Sensors, Transducers
Pressure Type Operating Pressure 5.8 PSI (40 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 120 mV (5V) Accuracy ±2% Voltage - Supply 1 V ~ 5 V Port Size - Port Style No Port Features - Termination Style Maximum Pressure Absolute 5.8 PSI (40 kPa) Wheatstone Bridge 0 mV ~ 120 mV (5V) +2% No Port 5 V Solder Pad 43.51 PSI (300 kPa)	Package	Die
Operating Pressure 5.8 PSI (40 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 120 mV (5V) Accuracy ±2% Voltage - Supply 1 V ~ 5 V Port Size - Port Style No Port Features - Termination Style Maximum Pressure 5.8 PSI (40 kPa) No mV ~ 120 mV (5V) - 5.8 PSI (40 kPa) No Port 5.8 PSI (40 kPa) No Port 5.8 PSI (40 kPa) No Port 42% 5.8 PSI (40 kPa) Solder Pad 43.51 PSI (300 kPa)	Series	C27
Output TypeWheatstone BridgeOutput0 mV ~ 120 mV (5V)Accuracy±2%Voltage - Supply1 V ~ 5 VPort Size-Port StyleNo PortFeatures-Termination StyleSolder PadMaximum Pressure43.51 PSI (300 kPa)	Pressure Type	Absolute
Output $0 \text{ mV} \sim 120 \text{ mV} (5\text{V})$ Accuracy $\pm 2\%$ Voltage - Supply $1 \text{ V} \sim 5 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StyleSolder PadMaximum Pressure $43.51 \text{ PSI } (300 \text{ kPa})$	Operating Pressure	5.8 PSI (40 kPa)
Accuracy $\pm 2\%$ Voltage - Supply $1 \text{ V} \sim 5 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StyleSolder PadMaximum Pressure $43.51 \text{ PSI } (300 \text{ kPa})$	Output Type	Wheatstone Bridge
Voltage - Supply Port Size Port Style No Port Features - Termination Style Maximum Pressure 1 V ~ 5 V No Port Solder Pad 43.51 PSI (300 kPa)	Output	$0 \text{ mV} \sim 120 \text{ mV} (5\text{V})$
Port Size - Port Style No Port Features - Termination Style Solder Pad Maximum Pressure 43.51 PSI (300 kPa)	Accuracy	±2%
Port Style No Port Features - Termination Style Solder Pad Maximum Pressure 43.51 PSI (300 kPa)	Voltage - Supply	1 V ~ 5 V
Features - Termination Style Solder Pad Maximum Pressure 43.51 PSI (300 kPa)	Port Size	-
Termination Style Solder Pad Maximum Pressure 43.51 PSI (300 kPa)	Port Style	No Port
Maximum Pressure 43.51 PSI (300 kPa)	Features	-
	Termination Style	Solder Pad
Operating Temperature -40°C ~ 135°C	Maximum Pressure	43.51 PSI (300 kPa)
- T · · · · O · · T · · · · · · · · · · ·	Operating Temperature	-40°C ~ 135°C
Package / Case Die	Package / Case	Die
Supplier Device Package Die	Supplier Device Package	Die
Report errors?		Report errors?

B58600C5010A004 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B58600C5010A004 Payment Methods





















B58600C5010A004 Shipping Methods













If you have any question about B58600C5010A004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com