



B81130B1224M Information



For Reference Only

Part Number B81130B1224M
Manufacturer EPCOS (TDK)
Category Capacitors
Film Capacitors

Description CAP FILM 0.22UF 20% 275VAC RAD

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B81130B1224M Specifications

Manufacturer Part Number B81130B1224M Manufacturer EPCOS (TDK) Category Capacitors Film Capacitors Package Radial Series B81130 Capacitance 0.22µF Tolerance ±20% Voltage Rating - AC 275V Voltage Rating - DC - Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	•	
Category Capacitors Film Capacitors Package Radial Series B81130 Capacitance 0.22μF Tolerance ±20% Voltage Rating - AC 275 V Voltage Rating - DC - Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Manufacturer Part Number	B81130B1224M
Film Capacitors Package Radial Series B81130 Capacitance 0.22μF Tolerance ±20% Voltage Rating - AC 275 V Voltage Rating - DC - Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Manufacturer	EPCOS (TDK)
PackageRadialSeriesB81130Capacitance 0.22μ FTolerance $\pm 20\%$ Voltage Rating - AC $275V$ Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature -40° C ~ 100° CMounting TypeThrough HolePackage / CaseRadialSize / Dimension 1.043° L x 0.276° W (26.50mm x 7.00mm)Height - Seated (Max) 0.630° (16.00mm)TerminationPC PinsLead Spacing 0.886° (22.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Category	Capacitors
Series B81130 Capacitance 0.22μF Tolerance ±20% Voltage Rating - AC 275 V Voltage Rating - DC - Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated		Film Capacitors
Capacitance $0.22\mu F$ Tolerance $\pm 20\%$ Voltage Rating - AC $275V$ Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature $-40^{\circ}C \sim 100^{\circ}C$ Mounting TypeThrough HolePackage / CaseRadialSize / Dimension 1.043° L x 0.276° W (26.50mm x 7.00mm)Height - Seated (Max) 0.630° (16.00mm)TerminationPC PinsLead Spacing 0.886° (22.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Package	Radial
Tolerance ±20% Voltage Rating - AC 275V Voltage Rating - DC - Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Series	B81130
Voltage Rating - AC Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Capacitance	0.22μF
Voltage Rating - DC Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Tolerance	±20%
Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications Features X2 Safety Rated	Voltage Rating - AC	275V
ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Voltage Rating - DC	-
Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Dielectric Material	Polypropylene (PP), Metallized
Mounting Type Through Hole Package / Case Radial Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.043" L x 0.276" W (26.50mm x 7.00mm)Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Operating Temperature	-40°C ~ 100°C
Size / Dimension 1.043" L x 0.276" W (26.50mm x 7.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Mounting Type	Through Hole
Height - Seated (Max) Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Yeatures X2 Safety Rated	Package / Case	Radial
Termination PC Pins Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Size / Dimension	1.043" L x 0.276" W (26.50mm x 7.00mm)
Lead Spacing 0.886" (22.50mm) Applications EMI, RFI Suppression Features X2 Safety Rated	Height - Seated (Max)	0.630" (16.00mm)
Applications EMI, RFI Suppression Features X2 Safety Rated	Termination	PC Pins
Features X2 Safety Rated	Lead Spacing	0.886" (22.50mm)
·	Applications	EMI, RFI Suppression
Report errors?	Features	X2 Safety Rated
		Report errors?

B81130B1224M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B81130B1224M Payment Methods



















B81130B1224M Shipping Methods













If you have any question about B81130B1224M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com