



B82467G153M Information

Heisener.com

Part Number B82467G153M **Manufacturer** EPCOS (TDK)

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 15UH 460MA 690 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B82467G153M Specifications

| Manufacturer EPCOS (TDK) Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series B82467G0 Type Wirewound Material - Core Ferrite Inductance 15µH Tolerance ±20% Current Rating 460mA Current - Saturation 370mA Shielding Shielded DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - Size / Dimension 0.110" L x 0.102" W (2.80mm x 2.60mm) | Manufacturer Part Number | B82467G153M |
|--|---------------------------|---------------------------------------|
| Fixed Inductors Package Nonstandard Series B82467G0 Type Wirewound Material - Core Ferrite Inductance 15μH Tolerance ±20% Current Rating 460mA Current - Saturation 370mA Shielding Shielded DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Manufacturer | EPCOS (TDK) |
| Package Nonstandard Series B82467G0 Type Wirewound Material - Core Ferrite Inductance 15μH Tolerance ±20% Current Rating 460mA Current - Saturation 370mA Shielding Shielded DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Category | Inductors, Coils, Chokes |
| Series B82467G0 Type Wirewound Material - Core Ferrite Inductance 15µH Tolerance ±20% Current Rating 460mA Current - Saturation 370mA Shielding Shielded DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | | Fixed Inductors |
| TypeWirewoundMaterial - CoreFerriteInductance15μHTolerance±20%Current Rating460mACurrent - Saturation370mAShieldingShieldedDC Resistance (DCR)690 mOhmQ @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-55°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package- | Package | Nonstandard |
| Material - Core Ferrite Inductance 15µH Tolerance ±20% Current Rating 460mA Current - Saturation 370mA Shielding Shielded DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Series | B82467G0 |
| Inductance15μHTolerance±20%Current Rating460mACurrent - Saturation370mAShieldingShieldedDC Resistance (DCR)690 mOhmQ @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-55°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package- | Type | Wirewound |
| Tolerance ±20% Current Rating 460mA Current - Saturation 370mA Shielding Shielded DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Material - Core | Ferrite |
| Current Rating 460mA Current - Saturation 370mA Shielding Shielded DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Inductance | 15μΗ |
| Current - Saturation 370mA Shielding Shielded DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Tolerance | ±20% |
| Shielding DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package - | Current Rating | 460mA |
| DC Resistance (DCR) 690 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Current - Saturation | 370mA |
| Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Shielding | Shielded |
| Frequency - Self Resonant Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | DC Resistance (DCR) | 690 mOhm |
| Ratings - Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Q @ Freq | - |
| Operating Temperature -55°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Frequency - Self Resonant | - |
| Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Ratings | - |
| Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Operating Temperature | -55°C ~ 125°C |
| Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - | Frequency - Test | 100kHz |
| Package / Case Nonstandard Supplier Device Package - | Features | - |
| Supplier Device Package - | Mounting Type | Surface Mount |
| | Package / Case | Nonstandard |
| Size / Dimension 0.110" L x 0.102" W (2.80mm x 2.60mm) | Supplier Device Package | - |
| | Size / Dimension | 0.110" L x 0.102" W (2.80mm x 2.60mm) |

Height - Seated (Max) 0.039" (1.00mm) Report errors?

B82467G153M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B82467G153M Payment Methods



















B82467G153M Shipping Methods













If you have any question about B82467G153M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com