

BAV70

BAV70 Information



Part Number	BAV70	
Manufacturer	Panasonic Electronic Components	
Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays	
Description	DIODE ARRAY GP 80V 200MA SOT23-3	
Package	TO-236-3, SC-59, SOT-23-3	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BAV70 Specifications

Manufacturer Part NumberBAV70ManufacturerPanasonic Electronic ComponentsCategoryDiscrete Semiconductor ProductsDades - Rectifiers - ArraysDiodes - Rectifiers - ArraysPackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)SpeedSmall Signal =< 200mA (Jo), Any SpeedReverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100nA @ 80VOperating Temperature - JunctionStarface MountMounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSot-23-3Supplier Device PackageSot-23-		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Manufacturer Part Number	BAV70
PackageDiodes - Rectifiers - ArraysPackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Manufacturer	Panasonic Electronic Components
PackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Category	Discrete Semiconductor Products
Series-Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Package	TO-236-3, SC-59, SOT-23-3
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Series	-
Voltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Voltage - DC Reverse (Vr) (Max)	80V
SpeedSmall Signal =< 200mA (Io), Any SpeedReverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100nA @ 80VOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23-3	Current - Average Rectified (Io) (per Diode)	200mA (DC)
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100nA @ 80VOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23-3	Voltage - Forward (Vf) (Max) @ If	1.25V @ 150mA
Current - Reverse Leakage @ Vr100nA @ 80VOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23-3	Speed	Small Signal =< 200mA (Io), Any Speed
Operating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23-3	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23-3	Current - Reverse Leakage @ Vr	100nA @ 80V
Package / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23-3	Operating Temperature - Junction	150°C (Max)
Supplier Device Package SOT-23-3	Mounting Type	Surface Mount
	Package / Case	TO-236-3, SC-59, SOT-23-3
Report err	Supplier Device Package	SOT-23-3
		Report errors?

BAV70 Guarantees



If you have any question about BAV70, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com