

BAW 56 B5003

Request a Quote

BAW 56 B5003 Information

www.telseour.com	Part Number	BAW 56 B5003	
	Manufacturer	Infineon Technologies	Γ
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays	Ŗ
	Description	DIODE ARRAY GP 80V 200MA SOT23	Ē
	Package	TO-236-3, SC-59, SOT-23-3	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BAW 56 B5003 Specifications

Manufacturer Part NumberBAW 56 B5003ManufacturerInfineon TechnologiesCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysDiodes - Rectifiers - ArraysPackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Common AnodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any SpeedReverse Recovery Time (trr)4nsQuerting Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Package / CasePace Anore		
CategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Common AnodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Manufacturer Part Number	BAW 56 B5003
Diodes - Rectifiers - ArraysPackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Common AnodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Manufacturer	Infineon Technologies
PackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Common AnodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Category	Discrete Semiconductor Products
Series-Diode Configuration1 Pair Common AnodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common AnodeDiode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Package	TO-236-3, SC-59, SOT-23-3
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Series	-
Voltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Diode Configuration	1 Pair Common Anode
Current - Average Rectified (Io) (per Diode) 200mA (DC) Voltage - Forward (Vf) (Max) @ If 1.25V @ 150mA Speed Small Signal =< 200mA (Io), Any Speed	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Voltage - DC Reverse (Vr) (Max)	80V
SpeedSmall Signal =< 200mA (Io), Any SpeedReverse Recovery Time (trr)4nsCurrent - Reverse Leakage @ Vr150nA @ 70VOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Current - Average Rectified (Io) (per Diode)	200mA (DC)
Reverse Recovery Time (trr)4nsCurrent - Reverse Leakage @ Vr150nA @ 70VOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Voltage - Forward (Vf) (Max) @ If	1.25V @ 150mA
Current - Reverse Leakage @ Vr150nA @ 70VOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Speed	Small Signal =< 200mA (Io), Any Speed
Operating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Reverse Recovery Time (trr)	4ns
Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Current - Reverse Leakage @ Vr	150nA @ 70V
Package / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Operating Temperature - Junction	150°C (Max)
Supplier Device Package PG-SOT23-3	Mounting Type	Surface Mount
	Package / Case	TO-236-3, SC-59, SOT-23-3
Perpet errors	Supplier Device Package	PG-SOT23-3
Report errors		Report errors?

BAW 56 B5003 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BAW 56 B5003 Payment Methods



BAW 56 B5003 Shipping Methods



If you have any question about BAW 56 B5003, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com