



BBD-06PMFS-QC8001 Information



For Reference Only

Part Number BBD-06PMFS-QC8001

Manufacturer Amphenol LTW

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG FMALE 6POS GOLD SOLDER

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BBD-06PMFS-QC8001 Specifications

Manufacturer Part Number BBD-06PMFS-QC8001 Manufacturer Amphenol LTW Category Connectors, Interconnects Package - Series X-Lok Connector Type Plug, Female Sockets Number of Positions 6 (4 Data + 2 Power) Shell Size - Insert B Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A		
CategoryConnectors, InterconnectsPackage-SeriesX-LokConnector TypePlug, Female SocketsNumber of Positions6 (4 Data + 2 Power)Shell Size - InsertBShell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeatures-Voltage - Rated30V, 300VAC/DCCurrent Rating5A, 10A	Manufacturer Part Number	BBD-06PMFS-QC8001
Package-SeriesX-LokConnector TypePlug, Female SocketsNumber of Positions6 (4 Data + 2 Power)Shell Size - InsertBShell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeatures-Voltage - Rated30V, 300VAC/DCCurrent Rating5A, 10A	Manufacturer	Amphenol LTW
Package-SeriesX-LokConnector TypePlug, Female SocketsNumber of Positions6 (4 Data + 2 Power)Shell Size - InsertBShell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeatures-Voltage - Rated30V, 300VAC/DCCurrent Rating5A, 10A	Category	Connectors, Interconnects
SeriesX-LokConnector TypePlug, Female SocketsNumber of Positions6 (4 Data + 2 Power)Shell Size - InsertBShell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeatures-Voltage - Rated30V, 300VAC/DCCurrent Rating5A, 10A		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 6 (4 Data + 2 Power) Shell Size - Insert B Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Package	-
Number of Positions6 (4 Data + 2 Power)Shell Size - InsertBShell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeatures-Voltage - Rated30V, 300VAC/DCCurrent Rating5A, 10A	Series	X-Lok
Shell Size - InsertBShell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeatures-Voltage - Rated30V, 300VAC/DCCurrent Rating5A, 10A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Number of Positions	6 (4 Data + 2 Power)
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Shell Size - Insert	В
Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation Keyed Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Termination	Solder Cup
Ingress Protection IP68 - Dust Tight, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Polyamide (PA), Nylon, Glass Filled Gold - 5A, 10A	Orientation	Keyed
Contact Finish Gold Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Ingress Protection	IP68 - Dust Tight, Waterproof
Features - Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Shell Material, Finish	Polyamide (PA), Nylon, Glass Filled
Voltage - Rated 30V, 300VAC/DC Current Rating 5A, 10A	Contact Finish	Gold
Current Rating 5A, 10A	Features	-
•	Voltage - Rated	30V, 300VAC/DC
Report errors?	Current Rating	5A, 10A
		Report errors?

BBD-06PMFS-QC8001 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BBD-06PMFS-QC8001 Payment Methods





















BBD-06PMFS-QC8001 Shipping Methods













If you have any question about BBD-06PMFS-QC8001, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com