

BCR20CM-12LB#BB0

BCR20CM-12LB#BB0 Information



For Reference Only

Part NumberBCR20CM-12LB#BB0ManufacturerRenesas Electronics AmericaCategoryDiscrete Semiconductor Products

Thyristors - TRIACs

Description TRIAC 800V 20A

Package TO-220-3

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BCR20CM-12LB#BB0 Specifications

Manufacturer Part Number Manufacturer Renesas Electronics America Category Discrete Semiconductor Products Thyristors - TRIACs Package TO-220-3 Series - Triac Type Standard Voltage - Off State Current - On State (It (RMS)) (Max) - Voltage - Gate Trigger (Vgt) (Max) - Current - Non Rep. Surge 50, 60Hz (Itsm) Current - Gate Trigger (Igt) (Max) - Current - Hold (Ih) (Max) - Current - Hold (Ih) (Max) Configuration Operating Temperature A0°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case Supplier Device Package		
Category Discrete Semiconductor Products Thyristors - TRIACs Package TO-220-3 Series - Triac Type Standard Voltage - Off State - Current - On State (It (RMS)) (Max) - Voltage - Gate Trigger (Vgt) (Max) - Current - Non Rep. Surge 50, 60Hz (Itsm) - Current - Gate Trigger (Igt) (Max) - Current - Hold (Ih) (Max) - Configuration Operating Temperature Mounting Type Through Hole Package / Case Supplier Device Package TO-220AB	Manufacturer Part Number	BCR20CM-12LB#BB0
Package TO-220-3 Series - Current - On State (It (RMS)) (Max) - Current - Non Rep. Surge 50, 60Hz (Itsm) - Current - Hold (Ih) (Max) - Curren	Manufacturer	Renesas Electronics America
Package TO-220-3 Series - Current - On State (It (RMS)) (Max) - Current - Non Rep. Surge 50, 60Hz (Itsm) - Current - Gate Trigger (Igt) (Max) - Current - Hold (Ih) (Max)	Category	Discrete Semiconductor Products
Series - Current - On State (It (RMS)) (Max) - Current - Non Rep. Surge 50, 60Hz (Itsm) - Current - Gate Trigger (Igt) (Max) - Current - Gate Trigger (Igt) (Max) - Current - Hold (Ih) (Max) - Configuration - Through Hole - 40°C ~ 150°C (TJ) - Through Hole - Package / Case - TO-220-3 - Supplier Device Package - TO-220AB		Thyristors - TRIACs
Triac Type Voltage - Off State Current - On State (It (RMS)) (Max) Voltage - Gate Trigger (Vgt) (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) - Current - Gate Trigger (Igt) (Max) Current - Hold (Ih) (Max) - Current - Hold (Ih) (Max) Configuration Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package	Package	TO-220-3
Voltage - Off State Current - On State (It (RMS)) (Max) Voltage - Gate Trigger (Vgt) (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) Current - Gate Trigger (Igt) (Max) - Current - Hold (Ih) (Max) Current - Hold (Ih) (Max) Configuration Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package	Series	-
Current - On State (It (RMS)) (Max) Voltage - Gate Trigger (Vgt) (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) Current - Gate Trigger (Igt) (Max) Current - Hold (Ih) (Max) Current - Hold (Ih) (Max) Configuration Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package	Triac Type	Standard
Voltage - Gate Trigger (Vgt) (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) - Current - Gate Trigger (Igt) (Max) - Current - Hold (Ih) (Max) - Configuration Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package	Voltage - Off State	-
Current - Non Rep. Surge 50, 60Hz (Itsm) Current - Gate Trigger (Igt) (Max) - Current - Hold (Ih) (Max) Configuration Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package	Current - On State (It (RMS)) (Max)	-
Current - Gate Trigger (Igt) (Max) Current - Hold (Ih) (Max) Configuration Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package	Voltage - Gate Trigger (Vgt) (Max)	-
Current - Hold (Ih) (Max) Configuration Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package TO-220AB	Current - Non Rep. Surge 50, 60Hz (Itsm)	-
Configuration Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package TO-220AB	Current - Gate Trigger (Igt) (Max)	-
Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package TO-220AB	Current - Hold (Ih) (Max)	-
Mounting Type Through Hole Package / Case TO-220-3 Supplier Device Package TO-220AB	Configuration	-
Package / Case TO-220-3 Supplier Device Package TO-220AB	Operating Temperature	-40°C ~ 150°C (TJ)
Supplier Device Package TO-220AB	Mounting Type	Through Hole
	Package / Case	TO-220-3
D (0	Supplier Device Package	TO-220AB
Report errors?		Report errors?

BCR20CM-12LB#BB0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BCR20CM-12LB#BB0 Payment Methods



















BCR20CM-12LB#BB0 Shipping Methods













If you have any question about BCR20CM-12LB#BB0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com