

BCS-131-L-D-TE-033

BCS-131-L-D-TE-033 Information

| | Part Number Manufacturer | BCS-131-L-D-TE-033 | |
|--------------------|-----------------------------|---|-----------------|
| Heisener.com | Category | Connectors, Interconnects | |
| | | Rectangular Connectors - Headers, Receptacles, Female Sockets | |
| | Description | BOX CONNECTOR SOCKET STRIP | |
| | Package | - | 回惑は燃 |
| For Reference Only | | For the pricing/inventory/lead time, please contact | |
| | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BCS-131-L-D-TE-033 Specifications

| Manufacturer Part NumberBCS-131-L-D-TE-033ManufacturerSantec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesTiger Claw? BCSConnector TypeReceptacleContact TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions62Number of Positions Loaded61Pich - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOldContact Finish - MatingGoldContact Finish Thickness - MatingJujin (0.25µm)Contact Finish Thickness - MatingJujin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - PostJ12" (3.10mm)Operating Temperature-55°C - 125°CMaterial Flammability RatingUL94 V-0 | | |
|--|-----------------------------------|---|
| Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Tiger Claw? BCS Connector Type Receptacle Contact Type Receptacle Contact Type Board to Board Style Board to Board Number of Positions 62 Number of Positions Loaded 61 Number of Rows 2 Rew Spacing - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating Older Mounting Type Through Hole Termination Solder Contact Finish - Mating Oldin (0.52µm) Contact Finish Finkenses - Mating Iopin (0.25µm) Insulation Color Black Insulation Height 0.290" (7.37mm) Contact Length - Post 0.122" (3.10mm) | Manufacturer Part Number | BCS-131-L-D-TE-033 |
| Image: Part of the sector of | Manufacturer | Samtec Inc. |
| Package-SeriesTiger Clav? BCSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions62Number of Positions Loaded1Pitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeDiolor (2.54mm)YerninationSolderFarminationSolderForta Finish - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingIupin (0.25µm)Insulation ColorBlackInsulation Height0.290° (7.37mm)Contact Length - Post0.122° (3.10mm)Operating Temperature55° C~ 125°C | Category | Connectors, Interconnects |
| SeriesTiger Clav? BCSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions62Number of Positions Loaded61Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)Youngh TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIquin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm) | | Rectangular Connectors - Headers, Receptacles, Female Sockets |
| Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions62Number of Positions Loaded61Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.100 (0.25µm)Insulation ColorBlackInsulation Height0.200" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55° C ~ 125°C | Package | - |
| Contact TypeFemale SocketStyleBoard to BoardNumber of Positions62Number of Positions Loaded61Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.90" (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Series | Tiger Claw? BCS |
| StyleBoard to BoardStyleBoard to BoardNumber of Positions62Number of Positions Loaded61Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Connector Type | Receptacle |
| Number of Positions 62 Number of Positions Loaded 61 Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type 0.100" (2.54mm) Termination Solder Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.290" (7.37mm) Ontact Length - Post 0.122" (3.10mm) | Contact Type | Female Socket |
| Number of Positions Loaded61Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature55°C ~ 125°C | Style | Board to Board |
| Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIbuin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post5.5°C ~ 125°C | Number of Positions | 62 |
| Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Number of Positions Loaded | 61 |
| Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Pitch - Mating | 0.100" (2.54mm) |
| Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Number of Rows | 2 |
| TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Row Spacing - Mating | 0.100" (2.54mm) |
| Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Mounting Type | Through Hole |
| Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Termination | Solder |
| Contact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Fastening Type | Push-Pull |
| Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Contact Finish - Mating | Gold |
| Insulation Height 0.290" (7.37mm) Contact Length - Post 0.122" (3.10mm) Operating Temperature -55°C ~ 125°C | Contact Finish Thickness - Mating | 10μin (0.25μm) |
| Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C | Insulation Color | Black |
| Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ | Insulation Height | 0.290" (7.37mm) |
| | Contact Length - Post | 0.122" (3.10mm) |
| Material Flammability Rating UL94 V-0 | Operating Temperature | -55°C ~ 125°C |
| | Material Flammability Rating | UL94 V-0 |

| Contact Finish - Post | Tin | | |
|------------------------|-----|--------|---------|
| Mated Stacking Heights | - | | |
| Ingress Protection | - | | |
| Features | - | | |
| | | Report | errors? |

BCS-131-L-D-TE-033 Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BCS-131-L-D-TE-033 Payment Methods



If you have any question about BCS-131-L-D-TE-033, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com