

Heisener.com

For Reference Only

# **BCS-138-TM-D-DE-BE**

#### **BCS-138-TM-D-DE-BE Information**

Part Number BCS-138-TM-D-DE-BE

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** BOX CONNECTOR SOCKET STRIP

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **BCS-138-TM-D-DE-BE Specifications**

Manufacturer Part Number         BCS-138-TM-D-DE-BE           Manufacturer         Samtec Inc.           Category         Connectors, Interconnects           Package         -           Series         Tiger Claw? BCS           Connector Type         Receptacle, Bottom or Top Entry           Contact Type         Female Socket           Style         Board to Board           Number of Positions         76           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         -           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.290" (7.37mm)           Contact Length - Post         0.120" (3.05mm)           Operating Temperature         -55°C ~ 125°C           Material Flammability Rating         UL94 V-0				
Category         Connectors, Interconnects           Package         -           Series         Tiger Claw? BCS           Connector Type         Receptacle, Bottom or Top Entry           Contact Type         Female Socket           Style         Board to Board           Number of Positions         76           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Tin           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.290" (7.37mm)           Contact Length - Post         0.120" (3.05mm)           Operating Temperature         -55°C ~ 125°C	Manufacturer Part Number	BCS-138-TM-D-DE-BE		
Package       -         Series       Tiger Claw? BCS         Connector Type       Receptacle, Bottom or Top Entry         Contact Type       Female Socket         Style       Board to Board         Number of Positions       76         Number of Positions Loaded       All         Pitch - Mating       0.100" (2.54mm)         Number of Rows       2         Row Spacing - Mating       0.100" (2.54mm)         Mounting Type       Through Hole         Termination       Solder         Fastening Type       Push-Pull         Contact Finish - Mating       Tin         Contact Finish Thickness - Mating       -         Insulation Color       Black         Insulation Height       0.290" (7.37mm)         Contact Length - Post       0.120" (3.05mm)         Operating Temperature       -55°C ~ 125°C	Manufacturer	Samtec Inc.		
Package         -           Series         Tiger Claw? BCS           Connector Type         Receptacle, Bottom or Top Entry           Contact Type         Female Socket           Style         Board to Board           Number of Positions         76           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         -           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.290" (7.37mm)           Contact Length - Post         0.120" (3.05mm)           Operating Temperature         -55°C ~ 125°C	Category	Connectors, Interconnects		
SeriesTiger Claw? BCSConnector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions76Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector Type Receptacle, Bottom or Top Entry  Contact Type Female Socket  Style Board to Board  Number of Positions 76  Number of Positions Loaded All  Pitch - Mating 0.100" (2.54mm)  Number of Rows 2  Row Spacing - Mating 0.100" (2.54mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.290" (7.37mm)  Contact Length - Post 0.120" (3.05mm)  Operating Temperature -55°C ~ 125°C	Package	-		
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions76Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Series	Tiger Claw? BCS		
Style Board to Board  Number of Positions 76  Number of Positions Loaded All  Pitch - Mating 0.100" (2.54mm)  Number of Rows 2  Row Spacing - Mating 0.100" (2.54mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.290" (7.37mm)  Contact Length - Post 0.120" (3.05mm)  Operating Temperature -55°C ~ 125°C	Connector Type	Receptacle, Bottom or Top Entry		
Number of Positions 76  Number of Positions Loaded All  Pitch - Mating 0.100" (2.54mm)  Number of Rows 2  Row Spacing - Mating 0.100" (2.54mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.290" (7.37mm)  Contact Length - Post 0.120" (3.05mm)  Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket		
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board		
Pitch - Mating 0.100" (2.54mm)  Number of Rows 2  Row Spacing - Mating 0.100" (2.54mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.290" (7.37mm)  Contact Length - Post 0.120" (3.05mm)  Operating Temperature -55°C ~ 125°C	Number of Positions	76		
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All		
Row Spacing - Mating  Mounting Type  Through Hole  Termination  Solder  Fastening Type  Push-Pull  Contact Finish - Mating  Contact Finish Thickness - Mating  Insulation Color  Black  Insulation Height  0.290" (7.37mm)  Contact Length - Post  Operating Temperature  -55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)		
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2		
Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.290" (7.37mm)  Contact Length - Post 0.120" (3.05mm)  Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	0.100" (2.54mm)		
Fastening Type Push-Pull  Contact Finish - Mating Tin  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.290" (7.37mm)  Contact Length - Post 0.120" (3.05mm)  Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole		
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.290" (7.37mm) Contact Length - Post 0.120" (3.05mm) Operating Temperature -55°C ~ 125°C	Termination	Solder		
Contact Finish Thickness - Mating  Insulation Color  Black  Insulation Height  0.290" (7.37mm)  Contact Length - Post  0.120" (3.05mm)  Operating Temperature  -55°C ~ 125°C	Fastening Type	Push-Pull		
Insulation ColorBlackInsulation Height $0.290" (7.37mm)$ Contact Length - Post $0.120" (3.05mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish - Mating	Tin		
Insulation Height $0.290" (7.37 mm)$ Contact Length - Post $0.120" (3.05 mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	-		
Contact Length - Post $0.120" (3.05 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black		
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.290" (7.37mm)		
	Contact Length - Post	0.120" (3.05mm)		
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C		
	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Tin		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
			Report errors?

#### **BCS-138-TM-D-DE-BE Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **BCS-138-TM-D-DE-BE Payment Methods**



















## **BCS-138-TM-D-DE-BE Shipping Methods**













If you have any question about BCS-138-TM-D-DE-BE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com