

BCS-146-L-S-TE-035

BCS-146-L-S-TE-035 Information

Heisener.com Solarierocianolier	Part Number Manufacturer Category	Connectors, Interconnects	
	Description	Rectangular Connectors - Headers, Receptacles, Female Sockets BOX CONNECTOR SOCKET STRIP	
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BCS-146-L-S-TE-035 Specifications

ManufacturerSamtec Inc.CategoryConnectors, InterconnectsPackage-SeriesTiger Claw? BCSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions Loaded1Number of Rows1Rows Pacing - Manufact5000°Number of Rows1Rows Pacing - Mating5001°Nounging TypePinough HoleContact Finish - MatingGoldContact Finish - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.20° (7.37mm)Contact Length - Post0.122° (3.10mm)Operating Temperature-55° C~ 125°C		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesTiger Claw? BCSConnector TypeReceptacleContact TypeBoard to BoardStyleBoard to BoardNumber of Positions46Number of Positions Loaded1Number of Rows1Number of Rows0.100" (2.54mm)Number of Rows1Number of Rows5YerminationSolderFreininationSolderFortact Finish - MatingGoldContact Finish - MatingGoldStation ColorBackInsulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Store Targer55° C + 25°C	Manufacturer Part Number	BCS-146-L-S-TE-035
Image: Part of the sector of	Manufacturer	Samtec Inc.
Package-SeriesTiger Claw? BCSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions Loaded45Number of Rows1Number of Rows1Row Spacing - Mating-Mouting TypeOilou? 0.54mm)Yenning TypeSolderFreminationSolderFastening TypeOilou? 0.254mn)Contact Finish - MatingOidoutSolderSolderFastening TypeOidoutInsulation ColorBiackInsulation Height0.200"(7.37mm)Contact Fungh - Post0.122"(3.10mm)Solder Type SolderSolderSolder SolderSolder<	Category	Connectors, Interconnects
SeriesTiger Clav? BCSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions Loaded45Pitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSolderFreminationSolderForstening TypeOldoContact Finish - MatingGoldContact Finish - MatingGoldSolderInjun(0.25µm)Finsulation ColorBackContact Finish - Mating10µin (0.25µm)Insulation ColorBiackInsulation Flopst0.200° (3.7mm)Contact Length - Post0.122° (3.10mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions Loaded45Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.100" (2.5µm)Insulation ColorBlackInsulation Height0.200" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeFenale SocketStyleBoard to BoardNumber of Positions46Number of Positions Loaded45Pitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.290° (7.37mm)Contact Length - Post0.122° (3.10mm)	Series	Tiger Claw? BCS
StyleBoard to BoardStyleBoard to BoardNumber of Positions46Number of Positions Loaded45Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Connector Type	Receptacle
Number of Positions 46 Number of Positions Loaded 45 Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Jupin (0.25µm) Insulation Color Black Insulation Height 0.290" (7.37mm) Contact Length - Post 0.122" (3.10mm)	Contact Type	Female Socket
Number of Positions Loaded45Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIlpuin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIupin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post55°C ~ 125°C	Number of Positions	46
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	45
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIupin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.290" (7.37mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.290" (7.37mm) Contact Length - Post 0.122" (3.10mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	10µin (0.25µm)
Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.290" (7.37mm)
	Contact Length - Post	0.122" (3.10mm)
Material Flammability Pating III 04 V 0	Operating Temperature	-55°C ~ 125°C
UL94 V-U	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

BCS-146-L-S-TE-035 Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BCS-146-L-S-TE-035 Payment Methods



If you have any question about BCS-146-L-S-TE-035, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com