

Heisener.com

### **BD5G Information**

Part Number BD5G

Manufacturer Hammond Manufacturing

**Category** Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 20VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **BD5G Specifications**

Manufacturer Part NumberBD5GManufacturerHammond ManufacturingCategoryTransformersPackage-SeriesBDTypeLaminated CoreVoltage - Primary240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)830mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max20 VAMounting TypeChassis MountTermination StyleWire Leads, Quick ConnectSize / Dimension59.18mm L x 59.44mm WHeight - Seated (Max)50.29mmVoltage - Isolation-Weight1.2 lbs (544.3g)	-	
Category         Transformers           Package         -           Series         BD           Type         Laminated Core           Voltage - Primary         240V           Voltage - Secondary (Full Load)         24V           Current - Output (Max)         830mA           Primary Winding(s)         Single           Secondary Winding(s)         Single           Center Tap         No           Power - Max         20 VA           Mounting Type         Chassis Mount           Termination Style         Wire Leads, Quick Connect           Size / Dimension         59.18mm L x 59.44mm W           Height - Seated (Max)         50.29mm           Voltage - Isolation         -           Weight         1.2 lbs (544.3g)	Manufacturer Part Number	BD5G
Package - Series BD - Laminated Core Voltage - Primary 240V Voltage - Secondary (Full Load) 24V Current - Output (Max) 830mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 20 VA Mounting Type Chassis Mount Termination Style Wire Leads, Quick Connect Size / Dimension 59.18mm L x 59.44mm W Height - Seated (Max) 50.29mm Voltage - Isolation -  Weight	Manufacturer	Hammond Manufacturing
Package-SeriesBDTypeLaminated CoreVoltage - Primary240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)830mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max20 VAMounting TypeChassis MountTermination StyleWire Leads, Quick ConnectSize / Dimension59.18mm L x 59.44mm WHeight - Seated (Max)50.29mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Category	Transformers
SeriesBDTypeLaminated CoreVoltage - Primary240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)830mAPrimary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max20 VAMounting TypeChassis MountTermination StyleWire Leads, Quick ConnectSize / Dimension59.18mm L x 59.44mm WHeight - Seated (Max)50.29mmVoltage - Isolation-Weight1.2 lbs (544.3g)		Power Transformers
Type Laminated Core  Voltage - Primary 240V  Voltage - Secondary (Full Load) 24V  Current - Output (Max) 830mA  Primary Winding(s) Single  Secondary Winding(s) Single  Center Tap No  Power - Max 20 VA  Mounting Type Chassis Mount  Termination Style Wire Leads, Quick Connect  Size / Dimension 59.18mm L x 59.44mm W  Height - Seated (Max) 50.29mm  Voltage - Isolation -  Weight 1.2 lbs (544.3g)	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  20 VA  Mounting Type  Chassis Mount  Termination Style  Wire Leads, Quick Connect  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  Weight  24V  24V  Cavrent - Output (Max)  Single  Single  Chassis Mount  Chassis Mount  Wire Leads, Quick Connect  59.18mm L x 59.44mm W  1.2 lbs (544.3g)	Series	BD
Voltage - Secondary (Full Load)  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Weight  Single  No  Chassis Mount  Wire Leads, Quick Connect  59.18mm L x 59.44mm W  1.2 lbs (544.3g)	Туре	Laminated Core
Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Single  Center Tap  No  Power - Max  20 VA  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Wire Leads, Quick Connect  59.18mm L x 59.44mm W  Height - Seated (Max)  Voltage - Isolation  Veight  830mA  830mA  830mA  830mA  Single  No  20 VA  No  20 VA  Wire Leads, Quick Connect  59.18mm L x 59.44mm W  150.29mm  Voltage - Isolation  -  Weight	Voltage - Primary	240V
Primary Winding(s)  Secondary Winding(s)  Single  Center Tap  No  Power - Max  20 VA  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Size / Dimension  Weight  Single  No  Power - Max  20 VA  Wire Leads, Quick Connect  59.18mm L x 59.44mm W  50.29mm  Voltage - Isolation  -  Weight	Voltage - Secondary (Full Load)	24V
Secondary Winding(s)SingleCenter TapNoPower - Max20 VAMounting TypeChassis MountTermination StyleWire Leads, Quick ConnectSize / Dimension59.18mm L x 59.44mm WHeight - Seated (Max)50.29mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Current - Output (Max)	830mA
Center TapNoPower - Max20 VAMounting TypeChassis MountTermination StyleWire Leads, Quick ConnectSize / Dimension59.18mm L x 59.44mm WHeight - Seated (Max)50.29mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Primary Winding(s)	Single
Power - Max  Mounting Type  Chassis Mount  Termination Style  Wire Leads, Quick Connect  Size / Dimension  59.18mm L x 59.44mm W  Height - Seated (Max)  50.29mm  Voltage - Isolation  -  Weight  1.2 lbs (544.3g)	Secondary Winding(s)	Single
Mounting TypeChassis MountTermination StyleWire Leads, Quick ConnectSize / Dimension59.18mm L x 59.44mm WHeight - Seated (Max)50.29mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Center Tap	No
Termination Style Wire Leads, Quick Connect Size / Dimension 59.18mm L x 59.44mm W Height - Seated (Max) 50.29mm  Voltage - Isolation - Weight 1.2 lbs (544.3g)	Power - Max	20 VA
Size / Dimension59.18mm L x 59.44mm WHeight - Seated (Max)50.29mmVoltage - Isolation-Weight1.2 lbs (544.3g)	Mounting Type	Chassis Mount
Height - Seated (Max)  Voltage - Isolation  Weight  50.29mm  - 1.2 lbs (544.3g)	Termination Style	Wire Leads, Quick Connect
Voltage - Isolation - Weight 1.2 lbs (544.3g)	Size / Dimension	59.18mm L x 59.44mm W
Weight 1.2 lbs (544.3g)	Height - Seated (Max)	50.29mm
	Voltage - Isolation	-
Report errors?	Weight	1.2 lbs (544.3g)
1		Report errors?

### **BD5G Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **BD5G Payment Methods**





















## **BD5G Shipping Methods**













If you have any question about BD5G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com