



BE-4R125PG5DC Information

Heisener.com

Part Number BE-4R125PG5DC

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS GAUGE 125PSI 4VDC

Package Cylinder, Threaded

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BE-4R125PG5DC Specifications

Manufacturer Part NumberBE-4R125PG5DCManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackageCylinder, ThreadedSeries-Pressure TypeVented GaugeOperating Pressure125 PSI (861.84 kPa)Output TypeAnalog VoltageOutput100 mV ~ 900 mV (5V)Accuracy±2%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination StyleTerminal PinsMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-		
CategorySensors, TransducersPackageCylinder, ThreadedSeries-Pressure TypeVented GaugeOperating Pressure125 PSI (861.84 kPa)Output TypeAnalog VoltageOutput100 mV ~ 900 mV (5V)Accuracy±2%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination StyleTerminal PinsMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Manufacturer Part Number	BE-4R125PG5DC
Package Cylinder, Threaded Series - Pressure Type Vented Gauge Operating Pressure Output Type Analog Voltage Output 100 mV ~ 900 mV (5V) Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style Terminal Pins Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinder, ThreadedSeries-Pressure TypeVented GaugeOperating Pressure125 PSI (861.84 kPa)Output TypeAnalog VoltageOutput100 mV ~ 900 mV (5V)Accuracy±2%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination StyleTerminal PinsMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Category	Sensors, Transducers
Series-Pressure TypeVented GaugeOperating Pressure125 PSI (861.84 kPa)Output TypeAnalog VoltageOutput100 mV ~ 900 mV (5V)Accuracy±2%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination StyleTerminal PinsMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 125 PSI (861.84 kPa) Output Type Analog Voltage Output 100 mV ~ 900 mV (5V) Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style Terminal Pins Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package	Package	Cylinder, Threaded
Operating Pressure Output Type Analog Voltage Output 100 mV ~ 900 mV (5V) Accuracy ±2% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style Terminal Pins Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Supplier Device Package - Cutput Analog Voltage Analog Volt	Series	-
Output TypeAnalog VoltageOutput $100 \text{ mV} \sim 900 \text{ mV} (5\text{ V})$ Accuracy $\pm 2\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreadedFeatures-Termination StyleTerminal PinsMaximum Pressure $250 \text{ PSI } (1723.69 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseCylinder, ThreadedSupplier Device Package-	Pressure Type	Vented Gauge
Output $100 \text{ mV} \sim 900 \text{ mV} (5\text{V})$ Accuracy $\pm 2\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreadedFeatures-Termination StyleTerminal PinsMaximum Pressure $250 \text{ PSI } (1723.69 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseCylinder, ThreadedSupplier Device Package-	Operating Pressure	125 PSI (861.84 kPa)
Accuracy $\pm 2\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreadedFeatures-Termination StyleTerminal PinsMaximum Pressure $250 \text{ PSI } (1723.69 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseCylinder, ThreadedSupplier Device Package-	Output Type	Analog Voltage
Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Output	100 mV ~ 900 mV (5V)
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style Terminal Pins Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Accuracy	±2%
Port Style Threaded Features - Termination Style Terminal Pins Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Voltage - Supply	4.75 V ~ 5.25 V
Features - Termination Style Terminal Pins Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Port Style	Threaded
Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Features	-
Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Termination Style	Terminal Pins
Package / Case Cylinder, Threaded Supplier Device Package -	Maximum Pressure	250 PSI (1723.69 kPa)
Supplier Device Package -	Operating Temperature	-20°C ∼ 85°C
	Package / Case	Cylinder, Threaded
D ()	Supplier Device Package	-
Report errors?		Report errors?

BE-4R125PG5DC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BE-4R125PG5DC Payment Methods



















BE-4R125PG5DC Shipping Methods













If you have any question about BE-4R125PG5DC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com