



BF014G0152K-- Information



For Reference Only

Part Number BF014G0152K-- **Manufacturer** AVX Corporation

Category Capacitors Film Capacitors

Description CAP FILM 1500PF 10% 250VDC RAD

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BF014G0152K-- Specifications

Manufacturer Part Number BF014G0152K Manufacturer AVX Corporation Category Capacitors Package Radial Series BF Capacitance 1500pF Tolerance ±10% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	*	
Category Capacitors Film Capacitors Package Radial Series BF Capacitance 1500pF Tolerance ±10% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Manufacturer Part Number	BF014G0152K
Package Radial Series BF Capacitance 1500pF Tolerance ±10% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Manufacturer	AVX Corporation
PackageRadialSeriesBFCapacitance1500pFTolerance±10%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.098" W (7.50mm x 2.50mm)Height - Seated (Max)0.256" (6.50mm)TerminationPC PinsLead Spacing0.200" (5.08mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
Series BF Capacitance 1500pF Tolerance ±10% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -		Film Capacitors
Capacitance 1500pF Tolerance ±10% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Package	Radial
Tolerance ±10% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Series	BF
Voltage Rating - AC Voltage Rating - DC 250V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Capacitance	1500pF
Voltage Rating - DC Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications Features -	Tolerance	±10%
Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 100°C Mounting Type Mounting Type Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications Features -	Voltage Rating - AC	160V
ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications Features -	Voltage Rating - DC	250V
Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Dielectric Material	Polyester, Metallized
Mounting Type Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	ESR (Equivalent Series Resistance)	-
Package / Case Radial Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Operating Temperature	-55°C ~ 100°C
Size / Dimension 0.295" L x 0.098" W (7.50mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Mounting Type	Through Hole
Height - Seated (Max) Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Package / Case	Radial
Termination PC Pins Lead Spacing 0.200" (5.08mm) Applications General Purpose Features -	Size / Dimension	0.295" L x 0.098" W (7.50mm x 2.50mm)
Lead Spacing0.200" (5.08mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.256" (6.50mm)
Applications General Purpose Features -	Termination	PC Pins
Features -	Lead Spacing	0.200" (5.08mm)
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

BF014G0152K-- Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BF014G0152K-- Payment Methods



















BF014G0152K-- Shipping Methods













If you have any question about BF014G0152K--, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com