

BFC233848164

BFC233848164 Information

Heisener.com Gittal sevice statisties	 BFC233848164 Vishay BC Components Capacitors Film Capacitors CAP FILM 10UF 10% 800VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BFC233848164 Specifications

Manufacturer Part NumberBFC233848164ManufacturerVishay BC ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesMKP338 4Capacitance10µFTolerance±10%Voltage Rating - AC300VVoltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedDoperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.732° L x 1.181° W (44.00mm x 30.00mm)Height - Seated (Max)1.811° (46.00mm)TerminationPC PinsLead Spacing1.476° (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP338 4Capacitance10µFTolerance±10%Voltage Rating - AC300VVoltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsFM, RFI SuppressionFeaturesX2 Safety Rated	Manufacturer Part Number	BFC233848164
Filn CapacitorsPackageRadialSeriesMKP338 4Capacitance10μFTolerance±10%Voltage Rating - AC300VVoltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP38 4Capacitance10μFTolerance±10%Voltage Rating - AC300VVoltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)Lead SpacingCP insApplicationsEMI, RFI SuppressionApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Category	Capacitors
SeriesMKP338 4Series10µFCapacitance10µFTolerance±10%Voltage Rating - AC300VVoltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.512" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated		Film Capacitors
CapacitanceI0μFTolerance±10%Voltage Rating - AC300VVoltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeRatialPackage / CaseRatialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)PC PinsIterationPC PinsApplications1.476" (37.50mm)FeaturesS2 Safety RatedFeaturesX2 Safety Rated	Package	Radial
Tolerance±10%Voltage Rating - AC300VVoltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.712" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Series	MKP338 4
Voltage Rating - AC300VVoltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Capacitance	10µF
Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Tolerance	±10%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionKeituresX2 Safety Rated	Voltage Rating - AC	300V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Voltage Rating - DC	800V
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Operating Temperature	-55°C ~ 105°C
Size / Dimension1.732" L x 1.181" W (44.00mm x 30.00mm)Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Mounting Type	Through Hole
Height - Seated (Max)1.811" (46.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Package / Case	Radial
TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Size / Dimension	1.732" L x 1.181" W (44.00mm x 30.00mm)
Lead Spacing1.476" (37.50mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Height - Seated (Max)	1.811" (46.00mm)
ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Termination	PC Pins
Features X2 Safety Rated	Lead Spacing	1.476" (37.50mm)
	Applications	EMI, RFI Suppression
	Features	X2 Safety Rated
Report errors?		Report errors?

BFC233848164 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about BFC233848164, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com