

BFC238361362 Information

Heisener.com

Part Number BFC238361362

Manufacturer Vishay BC Components

Category Capacitors

Film Capacitors

Description CAP FILM 3600PF 5% 2KVDC RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BFC238361362 Specifications

Manufacturer Part NumberBFC238361362ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRadialSeriesMMKP383Capacitance3600pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Pulse, DV/DT	•	
Category Capacitors Film Capacitors Package Radial Series MMKP383 Capacitance 3600pF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm) Height - Seated (Max) 0.472" (12.00mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Pulse, DV/DT	Manufacturer Part Number	BFC238361362
PackageRadialSeriesMMKP383Capacitance3600pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Pulse, DV/DT	Manufacturer	Vishay BC Components
PackageRadialSeriesMMKP383Capacitance3600pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Pulse, DV/DT	Category	Capacitors
Series MMKP383 Capacitance 3600pF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm) Height - Seated (Max) 0.472" (12.00mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Pulse, DV/DT		Film Capacitors
Capacitance3600pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Pulse, DV/DT	Package	Radial
Tolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Pulse, DV/DT	Series	MMKP383
Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Pulse, DV/DT	Capacitance	3600pF
Voltage Rating - DC Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Termination PC Pins Lead Spacing Applications 2000V (2kV) Polypropylene (PP), Metallized Polypropylene (PP), Metallized - 0.47°C Notable (PP), Metallized Polypropylene (PP), Metallized Polypropylene (PP), Metallized - 0.47°C 105°C Through Hole Package / Case Radial 0.689" L x 0.236" W (17.50mm x 6.00mm) 0.472" (12.00mm) High Pulse, DV/DT	Tolerance	±5%
Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm) Height - Seated (Max) 0.472" (12.00mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Pulse, DV/DT	Voltage Rating - AC	700V
ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm) Height - Seated (Max) 0.472" (12.00mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Pulse, DV/DT	Voltage Rating - DC	2000V (2kV)
Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm) Height - Seated (Max) 7 C Pins Lead Spacing 0.591" (15.00mm) High Pulse, DV/DT	Dielectric Material	Polypropylene (PP), Metallized
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm) Height - Seated (Max) 0.472" (12.00mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Pulse, DV/DT	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Pulse, DV/DT	Operating Temperature	-55°C ~ 105°C
Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm) Height - Seated (Max) 0.472" (12.00mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Pulse, DV/DT	Mounting Type	Through Hole
Height - Seated (Max) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Pulse, DV/DT	Package / Case	Radial
Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Pulse, DV/DT	Size / Dimension	0.689" L x 0.236" W (17.50mm x 6.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsHigh Pulse, DV/DT	Height - Seated (Max)	0.472" (12.00mm)
Applications High Pulse, DV/DT	Termination	PC Pins
	Lead Spacing	0.591" (15.00mm)
	Applications	High Pulse, DV/DT
Features -	Features	-
Report errors?		Report errors?

BFC238361362 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BFC238361362 Payment Methods



















BFC238361362 Shipping Methods













If you have any question about BFC238361362, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com