

BFC238560562

BFC238560562 Information

Heisener.com	Part Number Manufacturer Category Description Package	BFC238560562 Vishay BC Components Capacitors Film Capacitors CAP FILM 5600PF 5% 2KVDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BFC238560562 Specifications

ManufacturerVishay BC ComponentsCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance5600pFVoltage Rating - AC700VVoltage Rating - DC200V (2kV)Dielectric Material-Opprating Temperature-55°C ~ 110°COpprating Type710°GPackage / Case6.689° L x 0.236° W (1.50mm x 6.00mm)Siz / Dimension0.689° L x 0.236° W (1.50mm x 6.00mm)Fingth - Seated (Max)0.47° (12.00mm)Auge Spacing0.51° (15.00mm)Applications0.51° (15.00mm)Case0.51° (15.00mm)Cas			
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance5600pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedSeries Resistance)-Operating Temperature-55°C ~ 110°CMouning TypeThrough HoleSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.547" (12.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer Part Number	BFC238560562	
Fin CapacitorsPackageRadialSeriesMKP385Capacitance5600pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689° L x 0.236° W (17.50mm x 6.00mm)Height - Seated (Max)0.472° (12.00mm)Per PinsDistrictionum)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components	
PackageRadialSeriesMKP385Capacitance5600pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)Per ImationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors	
Series MKP385 Series 5600pF Capacitance 5600pF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm) Height - Seated (Max) 0.472" (12.00mm) Lead Spacing 0.591" (15.00mm) Applications DS1" (15.00mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT		Film Capacitors	
Capacitance5600pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)PerinationCS91" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsScale L in C, Switching; High Pulse, DV/DTFeatures-	Package	Radial	
Tolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)Applications0.591" (15.00mm)Features-	Series	MKP385	
Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	5600pF	
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$	
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	700V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	2000V (2kV)	
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized	
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C	
Size / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial	
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.689" L x 0.236" W (17.50mm x 6.00mm)	
Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.472" (12.00mm)	
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins	
Features -	Lead Spacing	0.591" (15.00mm)	
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	
Report errors?	Features	-	
		Report errors?	

BFC238560562 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BFC238560562 Payment Methods



BFC238560562 Shipping Methods



If you have any question about BFC238560562, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com