

BFC241632004

BFC241632004 Information

| Heisener.com | BFC241632004 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.2UF 5% 63VDC RADIAL Radial For the pricing/inventory/lead time, please contact | |
|--------------------|--|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BFC241632004 Specifications

| Manufacturer Part Number BFC241632004 Manufacturer Vishay BC Components Category Capacitors Package Radial Series MKP416 Capacitance - Tolerance - Voltage Rating - AC - Voltage Rating - DC - Dielectric Material Polyproplene (PP), Metallized Ster Se Ses Ses Ses Ses Ses Ses Ses Ses Ses | | |
|--|------------------------------------|--|
| CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP416Capacitance-Colerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedDierating Temperature-Operating Type-Sto [°] C ~ 85°CMunting TypeRadialSiz / DimensionAcda'Height - Seated (Max)-Height - Seated (Max)-Applications-Parmination-Height - Seated (Max)-Applications-Features-Kategory-Applications< | Manufacturer Part Number | BFC241632004 |
| Fin CapacitorsPackageRadialSeriesMKP416Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492° L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472° (12.00mm)Termination9CP PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Manufacturer | Vishay BC Components |
| PackageRadialSeriesMKP416Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.394" (10.00mm)ApplicationsMigh Frequency, SwitchingHeatresLong Life | Category | Capacitors |
| SeriesMKP416Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeRadialPackage / CaseRadialSize / Dimension0492° L x 0.236° W (12.50mm x 6.00mm)Height - Seated (Max)0472° (12.00mm)FerminationPC PinsApplications0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | | Film Capacitors |
| Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropelne (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeRatialPackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)Lead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Package | Radial |
| Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Series | MKP416 |
| Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Capacitance | - |
| Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Tolerance | - |
| Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Voltage Rating - AC | - |
| ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Voltage Rating - DC | - |
| Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Dielectric Material | Polypropylene (PP), Metallized |
| Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | ESR (Equivalent Series Resistance) | - |
| Package / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Operating Temperature | -55°C ~ 85°C |
| Size / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Mounting Type | Through Hole |
| Height - Seated (Max)0.472" (12.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Package / Case | Radial |
| TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Size / Dimension | 0.492" L x 0.236" W (12.50mm x 6.00mm) |
| Lead Spacing0.394" (10.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Height - Seated (Max) | 0.472" (12.00mm) |
| ApplicationsHigh Frequency, SwitchingFeaturesLong Life | Termination | PC Pins |
| Features Long Life | Lead Spacing | 0.394" (10.00mm) |
| | Applications | High Frequency, Switching |
| Report errors? | Features | Long Life |
| | | Report errors? |

BFC241632004 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BFC241632004 Payment Methods



BFC241632004 Shipping Methods



If you have any question about BFC241632004, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com