

BFC241638203

equest a Quote

BFC241638203 Information

Heisener.com	Part Number	BFC241638203
	Manufacturer	Vishay BC Components
	Category	Capacitors Film Capacitors
	Description	CAP FILM 0.082UF 5% 63VDC RADIAL
	Package	Radial
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BFC241638203 Specifications

Manufacturer Part Number BFC241638203 Manufacturer Vishay BC Components Category Capacitors Package Radial Series MKP416 Capacitance - Tolerance - Voltage Rating - AC - Voltage Rating - DC - Dielectric Material Polyproplene (PP), Metallized Special Type - Operating Type - Mounting Type - Package / Case Radial Size / Dimension 0.532° (13.50mm) Height - Seated (Max) 0.532° (13.50mm) Lead Spacing 0.591° (15.00mm) Applications High Frequency, Switching Features Long Life		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP416Capacitance-Colerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedDierating Temperature-Operating Type-55°C ~ 85°CMounting TypeRadialSiz / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)Height - Seated (Max)0.591" (15.00mm)ApplicationsMig Frequency, SwitchingFeaturesHigh Frequency, Switching	Manufacturer Part Number	BFC241638203
Film CapacitorsPackageRadialSeriesMKP416Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689° L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP416Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.639" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Category	Capacitors
SeriesMKP416Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-Mounting Type-55°C ~ 85°CNounting TypeRadialSize / Dimension0.532° (13.50mm x 7.00mm)Height - Seated (Max)0.532° (13.50mm)Lead Spacing0.591° (15.00mm)ApplicationsJigh Frequency, SwitchingFeaturesLong Life		Film Capacitors
Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeRatialPackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Package	Radial
Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Series	MKP416
Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Capacitance	-
Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Tolerance	-
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Voltage Rating - DC	-
Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Operating Temperature	-55°C ~ 85°C
Size / Dimension 0.689" L x 0.276" W (17.50mm x 7.00mm) Height - Seated (Max) 0.532" (13.50mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Frequency, Switching Features Long Life	Mounting Type	Through Hole
Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Size / Dimension	0.689" L x 0.276" W (17.50mm x 7.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Height - Seated (Max)	0.532" (13.50mm)
ApplicationsHigh Frequency, SwitchingFeaturesLong Life	Termination	PC Pins
Features Long Life	Lead Spacing	0.591" (15.00mm)
	Applications	High Frequency, Switching
Report errors?	Features	Long Life
		Report errors?

BFC241638203 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BFC241638203 Payment Methods



BFC241638203 Shipping Methods



If you have any question about BFC241638203, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com