

BFC241979103

BFC241979103 Information



Part Number	BFC241979103
Manufacturer	Vishay BC Components
Category	Capacitors Film Capacitors
Description	CAP FILM 0.091UF 2% 400VDC RAD
Package	Radial
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BFC241979103 Specifications

Manufacturer Part NumberBFC241979103ManufacturerVishay BC ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesMKP419Capacitance0.091µFTolerance±2%Voltage Rating - AC125VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadial	
CategoryCapacitorsFilm CapacitorsPackagePackageRadialSeriesCapacitanceOlog1μFToleranceVoltage Rating - ACVoltage Rating - DCDielectric MaterialPSR (Equivalent Series Resistance)-Operating TemperatureMounting TypeCategoryCategoryCapacitorsCapacitanceCapacitanceDielectric MaterialPolypropylene (PP), MetallizedCapacitance-Capacitance-Capacitance-Dielectric MaterialPackage-Capacitance-Capacitance<	
Film CapacitorsPackageRadialSeriesMKP419Capacitance0.091μFTolerance±2%Voltage Rating - AC125VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
PackageRadialSeriesMKP419Capacitance0.091μFTolerance±2%Voltage Rating - AC125VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
SeriesMKP419Capacitance0.091µFTolerance±2%Voltage Rating - AC125VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
Capacitance0.091µFTolerance±2%Voltage Rating - AC125VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
Tolerance±2%Voltage Rating - AC125VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
Voltage Rating - AC125VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
Voltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
Operating Temperature-55°C ~ 85°CMounting TypeThrough Hole	
Mounting Type Through Hole	
Package / Case Radial	
Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm)	
Height - Seated (Max) 0.472" (12.00mm)	
Termination PC Pins	
Lead Spacing 0.591" (15.00mm)	
Applications High Frequency, Switching	
Features -	
Report	errors?

BFC241979103 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BFC241979103 Payment Methods



BFC241979103 Shipping Methods



If you have any question about BFC241979103, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com