

BFC242003602

BFC242003602 Information

Heisener.com	 BFC242003602 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.0036UF 5% 630VDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BFC242003602 Specifications

Manufacturer Part NumberBFC242003602ManufacturerVishay BC ComponentsCategoryCapacitorsCategoryFilm CapacitorsPackageRadialSeriesMKP420Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeRatinalSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)		
CategoryCapacitorsFilm CapacitorsPackageRadialPackageRadialSeriesMKP420Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Voltage Temperature-55°C ~ 85°CMounting TypeRadialPackage / CaseRadialSize / Dimension0283" L x 0.138" W (7.20mm x 3.50mm)	Manufacturer Part Number	BFC242003602
Film CapacitorsPackageRadialSeriesMKP420Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Type-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Manufacturer	Vishay BC Components
PackageRadialPackageMKP420Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Type-55°C ~ 85°CMounting TypeFinough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Category	Capacitors
SeriesMKP420Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeFinough HolePackage / CaseRatialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)		Film Capacitors
Capacitance-Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeFhrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Package	Radial
Tolerance-Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeHrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Series	MKP420
Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Capacitance	-
Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Tolerance	-
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Voltage Rating - DC	-
Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.283" L x 0.138" W (7.20mm x 3.50mm)	Operating Temperature	-55°C ~ 85°C
Size / Dimension 0.283" L x 0.138" W (7.20mm x 3.50mm)	Mounting Type	Through Hole
	Package / Case	Radial
	Size / Dimension	0.283" L x 0.138" W (7.20mm x 3.50mm)
Height - Seated (Max) 0.728° (18.50mm)	Height - Seated (Max)	0.728" (18.50mm)
Termination PC Pins	Termination	PC Pins
Lead Spacing 0.197" (5.00mm)	Lead Spacing	0.197" (5.00mm)
Applications High Frequency, Switching	Applications	High Frequency, Switching
Features Long Life	Features	Long Life
Report errors ²		Report errors?

BFC242003602 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BFC242003602 Payment Methods



BFC242003602 Shipping Methods



If you have any question about BFC242003602, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com