

BFH 2A-12 Information

Heisener.com

Part Number BFH 2A-12

Manufacturer Comus International

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPST .5A 12V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BFH 2A-12 Specifications

Manufacturer Part Number BFH 2A-12 Manufacturer Comus International Category Relays Package - Series BFH Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms Features -		
Category Relays Signal Relays, Up to 2 Amps Package - Series BFH Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 200VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 0.5ms Release Time Relase Time	Manufacturer Part Number	BFH 2A-12
Package - Series BFH Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms	Manufacturer	Comus International
Package - Series BFH Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms	Category	Relays
SeriesBFHRelay TypeReedCoil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.15ms		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.15ms	Package	-
Coil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.15ms	Series	BFH
Coil Current 12mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms	Relay Type	Reed
Coil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.15ms	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms	Coil Current	12mA
Contact Rating (Current) Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms	Coil Voltage	12VDC
Switching Voltage 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.15ms	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 0.5ms Release Time 0.15ms	Switching Voltage	200VDC - Max
Operate Time 0.5ms Release Time 0.15ms	Turn On Voltage (Max)	9 VDC
Release Time 0.15ms	Turn Off Voltage (Min)	1 VDC
	Operate Time	0.5ms
Features -	Release Time	0.15ms
	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

BFH 2A-12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BFH 2A-12 Payment Methods



















BFH 2A-12 Shipping Methods













If you have any question about BFH 2A-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com