

BFP780H6327XTSA1

BFP780H6327XTSA1 Information





Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BFP780H6327XTSA1 Specifications

Manufacturer Part NumberBFP780H6327XTSA1ManufacturerInfineon TechnologiesCategoryDiscrete Semiconductor ProductsTransistors - Bipolar (BJT) - RFPackageSC-82A, SOT-343Series-Transistor TypeNPNVoltage - Collector Emitter Breakdown (Max)6.1VFrequency - Transition900MHzNoise Figure (dB Typ @ f)1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHzGain27dBPower - Max600mWDC Current Gain (hFE) (Min) @ Lc, Vce85 @ 90mA, 5VCurrent - Collector [L (Max)120mAOperating TemperatureSurface MountMounting TypeSurface MountPackage / CaseSC-82A, SOT-343		
CategoryDiscrete Semiconductor ProductsTransistors - Bipolar (BJT) - RFPackageSC-82A, SOT-343Series-Transistor TypeNPNVoltage - Collector Emitter Breakdown (Max)6.1VFrequency - Transition900MHzNoise Figure (dB Typ @ f)1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHzGain27dBPower - Max600mWDC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Manufacturer Part Number	BFP780H6327XTSA1
Transistors - Bipolar (BJT) - RFPackageSC-82A, SOT-343Series-Transistor TypeNPNVoltage - Collector Emitter Breakdown (Max)6.1VFrequency - Transition900MHzNoise Figure (dB Typ @ f)1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHzGain27dBPower - Max600mWDC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (L) (Max)120mAOperating Temperature50°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Manufacturer	Infineon Technologies
PackageSC-82A, SOT-343Series-Transistor TypeNPNVoltage - Collector Emitter Breakdown (Max)6.1VFrequency - Transition900MHzNoise Figure (dB Typ @ f)1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHzGain27dBPower - Max600mWDC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSc-82A, SOT-343	Category	Discrete Semiconductor Products
Series-Transistor TypeNPNVoltage - Collector Emitter Breakdown (Max)6.1VFrequency - Transition900MHzNoise Figure (dB Typ @ f)1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHzGain27dBPower - Max600mWDC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343		Transistors - Bipolar (BJT) - RF
Transistor TypeNPNVoltage - Collector Emitter Breakdown (Max)6.1VFrequency - Transition900MHzNoise Figure (dB Typ @ f)1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHzGain27dBPower - Max600mWDC Current Gain (hFE) (Min @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Package	SC-82A, SOT-343
Voltage - Collector Emitter Breakdown (Max)6.1VFrequency - Transition900MHzNoise Figure (dB Typ @ f)1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHzGain27dBPower - Max600mWDC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Series	-
Frequency - Transition900MHzNoise Figure (dB Typ @ f)1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHzGain27dBPower - Max600mWDC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Transistor Type	NPN
Noise Figure (dB Typ @ f)1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHzGain27dBPower - Max600mWDC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Voltage - Collector Emitter Breakdown (Max)	6.1V
Gain27dBPower - Max600mWDC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Frequency - Transition	900MHz
Power - Max600mWDC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Noise Figure (dB Typ @ f)	1.2dB ~ 2.4dB @ 900MHz ~ 3.5GHz
DC Current Gain (hFE) (Min) @ Ic, Vce85 @ 90mA, 5VCurrent - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Gain	27dB
Current - Collector (Ic) (Max)120mAOperating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Power - Max	600mW
Operating Temperature150°C (TJ)Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	DC Current Gain (hFE) (Min) @ Ic, Vce	85 @ 90mA, 5V
Mounting TypeSurface MountPackage / CaseSC-82A, SOT-343	Current - Collector (Ic) (Max)	120mA
Package / Case SC-82A, SOT-343	Operating Temperature	150°C (TJ)
	Mounting Type	Surface Mount
	Package / Case	SC-82A, SOT-343
Supplier Device Package SOT343-4-2	Supplier Device Package	SOT343-4-2
Report error		Report errors?

E-mail: salesdept@heisener.com

BFP780H6327XTSA1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

BFP780H6327XTSA1 Payment Methods



BFP780H6327XTSA1 Shipping Methods



If you have any question about BFP780H6327XTSA1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com