



BFR2029P1 Information

Part Number BFR2029P1

Manufacturer ITT Cannon, LLC

Category Heisener.com

Connectors, Interconnects **Circular Connectors**

Description

CONN RCPT 17POS W/PINS BULKHEAD

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BFR2029P1 Specifications

Manufacturer Part Number BFR2029P1 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-C-5015, BFR Connector Type Receptacle, Male Pins Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC		
Category Circular Connectors Package - Series MIL-C-5015, BFR Connector Type Receptacle, Male Pins Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Connectors, Interconnects Circular Connectors MIL-C-5015, BFR Receptacle, Male Pins MIL-C-5015, BFR Receptacle, Male Pins Neceptacle, Male Pins Normal Packet Packet Solder Cup Threaded Copientation N (Normal) Silver Features - Voltage - Rated SolovAC, 700VDC	Manufacturer Part Number	BFR2029P1
Circular Connectors Package - Series MIL-C-5015, BFR Connector Type Receptacle, Male Pins Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Convact Finish Convact Finish Silver Footward Solver	Manufacturer	ITT Cannon, LLC
Package - Series MIL-C-5015, BFR Connector Type Receptacle, Male Pins Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Category	Connectors, Interconnects
SeriesMIL-C-5015, BFRConnector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Package	-
Number of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Series	MIL-C-5015, BFR
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 20-29 Auninum, Bulkhead - Front Side Nut Environment Side Nut Solder Cup Threaded Aluminum, Olive Drab Cadmium Plated Silver Features - Voltage - Rated	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Number of Positions	17
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Shell Size - Insert	20-29
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Threaded N (Normal) Environment Resistant Aluminum, Olive Drab Cadmium Plated Silver 500VAC, 700VDC	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Aluminum, Olive Drab Cadmium Plated Silver - 500VAC, 700VDC	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Ingress Protection	Environment Resistant
Features - Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
	Features	-
Current Rating	Voltage - Rated	500VAC, 700VDC
Current Rating	Current Rating	-
Report errors?		Report errors?

BFR2029P1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BFR2029P1 Payment Methods





















BFR2029P1 Shipping Methods













If you have any question about BFR2029P1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com