



BFR24-28P-1 Information

Heisener.com

Part Number BFR24-28P-1 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 24POS W/PINS BULKHEAD

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BFR24-28P-1 Specifications

Manufacturer Part Number BFR24-28P-1 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-C-5015, BFR Connector Type Receptacle, Male Pins Number of Positions 24 Shell Size - Insert 24-28 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-C-5015, BFRConnector TypeReceptacle, Male PinsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer Part Number	BFR24-28P-1
Circular Connectors Package - Series MIL-C-5015, BFR Connector Type Receptacle, Male Pins Number of Positions 24 Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 200VAC, 250VDC Current Rating	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-C-5015, BFRConnector TypeReceptacle, Male PinsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesMIL-C-5015, BFRConnector TypeReceptacle, Male PinsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Series	MIL-C-5015, BFR
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Number of Positions	24
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Shell Size - Insert	24-28
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Silver - - - - - - - - - - - - -	Orientation	N (Normal)
Contact Finish Features - Voltage - Rated Current Rating Silver - 200VAC, 250VDC -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 200VAC, 250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

BFR24-28P-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BFR24-28P-1 Payment Methods





















BFR24-28P-1 Shipping Methods













If you have any question about BFR24-28P-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com