

## **BK/ABC-V-25 Information**



For Reference Only

Part Number BK/ABC-V-25

Manufacturer Eaton

Category Circuit Protection

Fuses

**Description** FUSE CERAMIC 25A 125VAC/VDC 3AB

**Package** 3AB, 3AG, 1/4" x 1-1/4" (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **BK/ABC-V-25 Specifications**

Manufacturer Part NumberBK/ABC-V-25ManufacturerEatonCategoryCircuit ProtectionFuses3AB, 3AG, 1/4" x 1-1/4" (Axial)SeriesABCFuse TypeCartridge, CeramicCurrent Rating25AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastPackage / Case3AB, 3AG, 1/4" x 1-1/4" (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1kA AC, 400A DCMelting 12t839.3ApprovalsCSA, ULOperating Temperature-Color-Size / Dimension0.266" Dia x 1.292" L (6.76mm x 32.82mm)	•	
Category         Circuit Protection           Fuses           Package         3AB, 3AG, 1/4" x 1-1/4" (Axial)           Series         ABC           Fuse Type         Cartridge, Ceramic           Current Rating         25A           Voltage Rating - AC         250V           Voltage Rating - DC         125V           Response Time         Fast           Package / Case         3AB, 3AG, 1/4" x 1-1/4" (Axial)           Mounting Type         Through Hole           Breaking Capacity @ Rated Voltage         1kA AC, 400A DC           Melting I2t         839.3           Approvals         CSA, UL           Operating Temperature         -           Color         -           Size / Dimension         0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Manufacturer Part Number	BK/ABC-V-25
Fuses           Package         3AB, 3AG, 1/4" x 1-1/4" (Axial)           Series         ABC           Fuse Type         Cartridge, Ceramic           Current Rating         25A           Voltage Rating - AC         250V           Voltage Rating - DC         125V           Response Time         Fast           Package / Case         3AB, 3AG, 1/4" x 1-1/4" (Axial)           Mounting Type         Through Hole           Breaking Capacity @ Rated Voltage         1kA AC, 400A DC           Melting 12t         839.3           Approvals         CSA, UL           Operating Temperature         -           Color         -           Size / Dimension         0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Manufacturer	Eaton
Package 3AB, 3AG, 1/4" x 1-1/4" (Axial)  Series ABC  Fuse Type Cartridge, Ceramic  Current Rating 25A  Voltage Rating - AC 250V  Voltage Rating - DC 125V  Response Time Fast  Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 1kA AC, 400A DC  Melting I2t 839.3  Approvals CSA, UL  Operating Temperature -  Color -  Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Category	Circuit Protection
Series ABC Fuse Type Cartridge, Ceramic Current Rating 25A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1kA AC, 400A DC Melting I2t 839.3 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)		Fuses
Fuse Type Current Rating 25A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 839.3 Approvals CSA, UL Operating Temperature Color Size / Dimension  Cartridge, Ceramic  25A  Cartridge, Ceramic 25A  250V  125V  Response Time Fast 3AB, 3AG, 1/4" x 1-1/4" (Axial)  ABA, 3AG, 1/4" x 1-1/4" (Axial)  CSA, UL  Operating Temperature  - Color - Size / Dimension  O.266" Dia x 1.292" L (6.76mm x 32.82mm)	Package	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Current Rating  Voltage Rating - AC  250V  Voltage Rating - DC  125V  Response Time  Fast  Package / Case  3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  839.3  Approvals  CSA, UL  Operating Temperature  Color  Size / Dimension  25A  250V  125V  125V  125V  Rated Voltage  Fast  3AB, 3AG, 1/4" x 1-1/4" (Axial)  Through Hole  1kA AC, 400A DC  839.3  CSA, UL  Operating Temperature  -  0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Series	ABC
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Package / Case  3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  1kA AC, 400A DC  Melting I2t  839.3  Approvals  CSA, UL  Operating Temperature  Color  Color  Size / Dimension  250V  125V	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC  Response Time  Fast  Package / Case  3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  1kA AC, 400A DC  Melting I2t  839.3  Approvals  CSA, UL  Operating Temperature  -  Color  Size / Dimension  125V  1	Current Rating	25A
Response Time Fast  Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 1kA AC, 400A DC  Melting I2t 839.3  Approvals CSA, UL  Operating Temperature -  Color -  Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 1kA AC, 400A DC  Melting I2t 839.3  Approvals CSA, UL  Operating Temperature -  Color -  Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Voltage Rating - DC	125V
Mounting Type  Breaking Capacity @ Rated Voltage  IkA AC, 400A DC  Melting I2t  Approvals  CSA, UL  Operating Temperature  Color  Size / Dimension  Through Hole  1kA AC, 400A DC  839.3  CSA, UL	Response Time	Fast
Breaking Capacity @ Rated Voltage  Melting I2t  839.3  Approvals  CSA, UL  Operating Temperature  Color  Size / Dimension  1kA AC, 400A DC  839.3  CSA, UL  -  0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Package / Case	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Melting I2t 839.3  Approvals CSA, UL  Operating Temperature - Color - Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Mounting Type	Through Hole
Approvals CSA, UL  Operating Temperature - Color - Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Breaking Capacity @ Rated Voltage	1kA AC, 400A DC
Operating Temperature         -           Color         -           Size / Dimension         0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Melting I2t	839.3
Color         -           Size / Dimension         0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Approvals	CSA, UL
Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Operating Temperature	-
	Color	-
Report errors?	Size / Dimension	0.266" Dia x 1.292" L (6.76mm x 32.82mm)
		Report errors?

### **BK/ABC-V-25 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **BK/ABC-V-25 Payment Methods**



















## **BK/ABC-V-25 Shipping Methods**













If you have any question about BK/ABC-V-25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com