

BK/JJS-3

BK/JJS-3 Information



Part Number	BK/JJS-3	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	CLASS T 3 AMP 600V	
Package	Cartridge, Non-Standard	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BK/JJS-3 Specifications

ManufacturerEatonCategoryCircuit ProtectionBeckageCartridge, Non-StandardPackageCartridge, Non-StandardSeriesJJSFuser TypeCartridgeCurrent RatingAVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200KAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension500° Dia x 1.500° W (14.22mm x 38.10mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesJJSFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassCE, CSA, ULOperating Temperature200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / DimensionStor" Dira 1.500" W (14.22mm x 38.10mm)	Manufacturer Part Number	BK/JJS-3
Current AsingElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesJJSFuse TypeCartridgeCurrent RatingSAVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSco" Dia x 1.500" W (14.22mm x 38.10mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesJJSFuse TypeCartridgeFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Category	Circuit Protection
SeriesJJSFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeFuse TypeGartridgeCurrent RatingGartridgeVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature200KABreaking Capacity @ Rated Voltage200KAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Package	Cartridge, Non-Standard
Current Rating3AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Series	ZLL
Voltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Current Rating	3A
Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Voltage Rating - AC	600V
ApplicationsElectrical, IndustrialApplications-Features-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Voltage Rating - DC	-
Features-Features-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Response Time	Fast
ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Class	Т
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.560" Dia x 1.500" W (14.22mm x 38.10mm)
		Report errors?

BK/JJS-3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about BK/JJS-3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com