



BK/MDA-V-8-R Information



For Reference Only

Part Number BK/MDA-V-8-R

Manufacturer Eaton

Category Circuit Protection

Fuses

Description FUSE CERAMIC 8A 250VAC 3AB 3AG

Package 3AB, 3AG, 1/4" x 1-1/4" (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BK/MDA-V-8-R Specifications

Manufacturer Part Number BK/MDA-V-8-R Manufacturer Eaton Category Circuit Protection Fuses Fuses Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series MDA Fuse Type Cartridge, Ceramic Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 200A Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature - Color -	*	
Category Circuit Protection Fuses Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series MDA Fuse Type Cartridge, Ceramic Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals CE, CSA, UL Operating Temperature - Color Circuit Protection Fuses 1038.4 Circuit Protection Fuses 1048.3 AG, 1/4" x 1-1/4" (Axial) Circuit Protection 1049.3 AB, 3AG, 1/4" x 1-1/4" (Axial) Circuit Protection 1058.4 CE, CSA, UL Operating Temperature - Color	Manufacturer Part Number	BK/MDA-V-8-R
Fuses Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series MDA Fuse Type Cartridge, Ceramic Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 200A Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature - Color -	Manufacturer	Eaton
Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series MDA Fuse Type Cartridge, Ceramic Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 200A Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature - Color -	Category	Circuit Protection
Series MDA Fuse Type Cartridge, Ceramic Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 200A Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature - Color -		Fuses
Fuse Type Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC	Package	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Current Rating 8A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 200A Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature - Color -	Series	MDA
Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, CSA, UL Operating Temperature Color - 250V 250V 250V - 1038.4 250V - Color - Color	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 200A Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature Color -	Current Rating	8A
Response Time Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 200A Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature Color	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 200A Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature - Color -	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, CSA, UL Operating Temperature Color Through Hole 200A CE, CSA, UL	Response Time	Slow
Breaking Capacity @ Rated Voltage 200A Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature - Color -	Package / Case	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Melting I2t 1038.4 Approvals CE, CSA, UL Operating Temperature - Color -	Mounting Type	Through Hole
Approvals CE, CSA, UL Operating Temperature - Color -	Breaking Capacity @ Rated Voltage	200A
Operating Temperature - Color -	Melting I2t	1038.4
Color -	Approvals	CE, CSA, UL
	Operating Temperature	-
Size / Dimension 0.266" Dia v. 1.292" I. (6.76mm v. 32.82mm)	Color	-
0.200 Dit x 1.252 D (0.7011111 x 32.0211111)	Size / Dimension	0.266" Dia x 1.292" L (6.76mm x 32.82mm)
Report errors?		Report errors?

BK/MDA-V-8-R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BK/MDA-V-8-R Payment Methods



















BK/MDA-V-8-R Shipping Methods













If you have any question about BK/MDA-V-8-R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com