

BK/MDL-1-1/4 Information



For Reference Only

Part Number BK/MDL-1-1/4

Manufacturer Eaton

Category Circuit Protection

Fuses

Description FUSE GLASS 1.25A 250VAC 3AB 3AG

Package 3AB, 3AG, 1/4" x 1-1/4"

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BK/MDL-1-1/4 Specifications

Manufacturer Part Number Manufacturer Category Circuit Protection Fuses Package Package ABA, 3AG, 1/4" x 1-1/4" Series MDL Fuse Type Cartridge, Glass Current Rating 1.25A Voltage Rating - AC Voltage Rating - DC Response Time Package / Case ABA, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, UL Operating Temperature Color Size / Dimension BK/MDL-1-1/4 Eaton Circuit Protection Fuses SaAB, 3AG, 1/4" x 1-1/4" MOL Siow Package / Case ABB, 3AG, 1/4" x 1-1/4" MOL CSA, UL Operating Temperature Color Size / Dimension Report errors?	•	
Category Circuit Protection Fuses 3AB, 3AG, 1/4" x 1-1/4" Series MDL Fuse Type Cartridge, Glass Current Rating 1.25A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 86.2 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Manufacturer Part Number	BK/MDL-1-1/4
Fuses 3AB, 3AG, 1/4" x 1-1/4" Series MDL	Manufacturer	Eaton
Package 3AB, 3AG, 1/4" x 1-1/4" Series MDL Fuse Type Cartridge, Glass Current Rating 1.25A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 86.2 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Category	Circuit Protection
Series MDL Fuse Type Cartridge, Glass Current Rating 1.25A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 86.2 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)		Fuses
Fuse Type Current Rating 1.25A Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Size / Dimension Cartridge, Glass 1.25A Cartridge, Glass 1.25A Logar Logar	Package	3AB, 3AG, 1/4" x 1-1/4"
Current Rating 1.25A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 86.2 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Series	MDL
Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Abar James	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, UL Operating Temperature Color Size / Dimension - Slow Slow 3AB, 3AG, 1/4" x 1-1/4" Holder COA COA 100A 86.2 CSA, UL COBI COBI	Current Rating	1.25A
Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 86.2 Approvals CSA, UL Operating Temperature - Color - Size / Dimension Slow AB, 3AG, 1/4" x 1-1/4" Color CSA, UL CSO'' Dia x 1.250" L (6.35mm x 31.75mm)	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 86.2 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Voltage Rating - DC	-
Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 86.2 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Response Time	Slow
Breaking Capacity @ Rated Voltage 100A Melting I2t 86.2 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Package / Case	3AB, 3AG, 1/4" x 1-1/4"
Melting I2t 86.2 Approvals CSA, UL Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Mounting Type	Holder
Approvals CSA, UL Operating Temperature Color Size / Dimension CSA, UL - 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Breaking Capacity @ Rated Voltage	100A
Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Melting I2t	86.2
Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Approvals	CSA, UL
Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Operating Temperature	-
	Color	-
Report errors?	Size / Dimension	0.250" Dia x 1.250" L (6.35mm x 31.75mm)
		Report errors?

BK/MDL-1-1/4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BK/MDL-1-1/4 Payment Methods

































If you have any question about BK/MDL-1-1/4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com