

BK/MDL-4/10 Information



For Reference Only

Part Number BK/MDL-4/10

Manufacturer Eaton

Category Circuit Protection

Fuses

Description FUSE GLASS 400MA 250VAC 3AB 3AG

Package 3AB, 3AG, 1/4" x 1-1/4"

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BK/MDL-4/10 Specifications

Manufacturer Part Number BK/MDL-4/10 Manufacturer Eaton Category Circuit Protection Package 3AB, 3AG, 1/4" x 1-1/4" Series MDL Fuse Type Cartridge, Glass Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage - Melting 12t - Approvals - Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm) Report errors?	•	
Category Circuit Protection Fuses Package 3AB, 3AG, 1/4" x 1-1/4" Series MDL Fuse Type Cartridge, Glass Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage - Melting I2t - Approvals - Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Manufacturer Part Number	BK/MDL-4/10
Package 3AB, 3AG, 1/4" x 1-1/4" Series MDL Fuse Type Cartridge, Glass Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage - Melting 12t - Approvals - Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Manufacturer	Eaton
Package 3AB, 3AG, 1/4" x 1-1/4" Series MDL Fuse Type Cartridge, Glass Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage - Melting I2t - Approvals - Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Category	Circuit Protection
Series MDL Fuse Type Cartridge, Glass Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage - Melting I2t - Approvals - Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)		Fuses
Fuse Type Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t - Approvals Operating Temperature Color Size / Dimension Cartridge, Glass 400mA 400mA 400mA 400mA 400mA - Saba 400mA - About 100m - Silow - Cartridge, Glass 400mA 400mA - Silow - Silow	Package	3AB, 3AG, 1/4" x 1-1/4"
Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage - Melting I2t - Approvals - Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Series	MDL
Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Approvals Operating Temperature Color Size / Dimension 250V	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage	Current Rating	400mA
Response Time Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Size / Dimension Slow 3AB, 3AG, 1/4" x 1-1/4" Holder - - - - - - - - - - - - -	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage - Melting I2t - Approvals - Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Size / Dimension Holder	Response Time	Slow
Breaking Capacity @ Rated Voltage - Melting I2t - Approvals - Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Package / Case	3AB, 3AG, 1/4" x 1-1/4"
Melting I2t - Approvals - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Mounting Type	Holder
Approvals - Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Breaking Capacity @ Rated Voltage	-
Operating Temperature - Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Melting I2t	-
Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Approvals	-
Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Operating Temperature	-
, , , , , , , , , , , , , , , , , , ,	Color	-
Report errors?	Size / Dimension	0.250" Dia x 1.250" L (6.35mm x 31.75mm)
		Report errors?

BK/MDL-4/10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BK/MDL-4/10 Payment Methods





















BK/MDL-4/10 Shipping Methods













If you have any question about BK/MDL-4/10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com