

BK/NON-60

Request a Quote

BK/NON-60 Information

Heisener.com Bittarierer satu tier	Part Number	BK/NON-60
	Manufacturer	Eaton
	Category	Circuit Protection Electrical, Specialty Fuses
	Description	BUSS ONE TIME FUSE
	Package	Cartridge, Non-Standard
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



BK/NON-60 Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardPackageNONFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ApprovalsCSA, ULOperating Temperature50kABreaking Capacity @ Rated Voltage50kAMunting TypeGutardige, Non-StandardPackage / CaseStartinge, Non-Standard		
CategoryCircuit ProtectionBeckageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesNONFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5Operating Temperature50kANonduring Type50kAMounting TypeFolderPackage / CaseScattridge, Non-StandardSize / DimensionStandardSize / DimensionStand	Manufacturer Part Number	BK/NON-60
Interform Billectrical, Specialty FusesPackageCartridge, Non-StandardSeriesNONFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature50kABreaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesNONFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Category	Circuit Protection
SeriesNONFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeFuse Type60ACurrent Rating60AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature50kAMounting Type50kAPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Package	Cartridge, Non-Standard
Current Rating60AVoltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Series	NON
Voltage Rating - AC250VVoltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / Case0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Fuse Type	Cartridge
Voltage Rating - DC125VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Current Rating	60A
Response Time-ApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Voltage Rating - AC	250V
ApplicationsElectrical, IndustrialApplications-Features-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Voltage Rating - DC	125V
Features-Features-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Response Time	-
ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Class	K5
Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.810" Dia x 3.00" L (20.57mm x 76.20mm)
		Report errors?

BK/NON-60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

BK/NON-60 Payment Methods Image: Im

If you have any question about BK/NON-60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com