

BK/S501-400-R Information



For Reference Only

Part Number BK/S501-400-R

Manufacturer Eaton

Category Circuit Protection

Fuses

Description FUSE CERAMIC 400MA 250VAC 5X20MM

Package 5mm x 20mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









BK/S501-400-R Specifications

Manufacturer Part NumberBK/S501-400-RManufacturerEatonCategoryCircuit ProtectionPackage5mm x 20mmSeriesS501Fuse TypeCartridge, CeramicCurrent Rating400mAVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastPackage / Case5mm x 20mmMounting TypeHolderBreaking Capacity @ Rated Voltage1.5kAMelting 12t0.018ApprovalsCSA, cULusOperating Temperature-Color-Size / Dimension0.205" Dia x 0.787" L (5.20mm x 20.00mm)Report errors?	•	
Category Circuit Protection Fuses Package 5mm x 20mm Series S501 Fuse Type Cartridge, Ceramic Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.018 Approvals CSA, cULus Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Manufacturer Part Number	BK/S501-400-R
Package 5mm x 20mm Series \$501 Fuse Type Cartridge, Ceramic Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 1.5kA Melting 12t 0.018 Approvals CSA, cULus Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Manufacturer	Eaton
Package 5mm x 20mm Series S501 Fuse Type Cartridge, Ceramic Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 1.5kA Melting 12t 0.018 Approvals CSA, cULus Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Category	Circuit Protection
Series \$501 Fuse Type Cartridge, Ceramic Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.018 Approvals CSA, cULus Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)		Fuses
Fuse Type Current Rating 400mA Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Size / Dimension Cartridge, Ceramic 400mA 600m Casturidge, Ceramic 400mA 400mA 600m Casturidge, Ceramic 600m - Cattridge, Ceramic 600mA 600mA 600mA 600m 600	Package	5mm x 20mm
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t 0.018 Approvals Operating Temperature Color Size / Dimension 400mA 400mm 400	Series	S501
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Size / Dimension 250V 250V 250V 250V 250V 250V 250V 250V - 0.000 Fast 5mm x 20mm Holder 1.5kA 0.018 0.018 CSA, cULus 0.018 - 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.018 Approvals Operating Temperature Color Size / Dimension - Color 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Current Rating	400mA
Response Time Fast Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.018 Approvals CSA, cULus Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Voltage Rating - AC	250V
Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.018 Approvals CSA, cULus Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Voltage Rating - DC	-
Mounting Type Holder Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.018 Approvals CSA, cULus Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Response Time	Fast
Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.018 Approvals CSA, cULus Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Package / Case	5mm x 20mm
Melting I2t0.018ApprovalsCSA, cULusOperating Temperature-Color-Size / Dimension0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Mounting Type	Holder
Approvals CSA, cULus Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Breaking Capacity @ Rated Voltage	1.5kA
Operating Temperature - Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Melting I2t	0.018
Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Approvals	CSA, cULus
Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Operating Temperature	-
	Color	-
Report errors?	Size / Dimension	0.205" Dia x 0.787" L (5.20mm x 20.00mm)
		Report errors?

BK/S501-400-R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

BK/S501-400-R Payment Methods



















BK/S501-400-R Shipping Methods













If you have any question about BK/S501-400-R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com